



















NQuire 1500 Mobula II

Touch Panel Computers

					
15.6" screen	1D & 2D	4G	Android 13	Bluetooth 5.2	Camera
					
I/O Ctrl	Megapixel	Ndevor	Optional MSR	Optional NFC	PoE
					
Touchscreen	USB	Warranty 2 Years	WiFi Dual Band		



Features

Extra Large Multi-Purpose Touch Screen

The NQuire 1500 Mobula II features a versatile 15.6" touchscreen, ensuring seamless interaction and user-friendly experience. With its extra large screen, the NQuire 1500 Mobula II allows you to effectively display extensive amounts of data and run third-party applications, serving diverse purposes like warehouse stock management, supermarket checkouts, or hotel self-check-in processes.

Robust Performance

Powered by 2.0GHz octa-core processor, the NQuire 1500 Mobula II is designed to handle dynamic environments. Operating on the Android 13 platform, the NQuire 1500 Mobula II facilitates the creation and seamless deployment of customized applications, leveraging the full potential of the feature-rich Android environment.

Full Wireless Features

Offering various connectivity options, including WiFi, Ethernet, Bluetooth 5.2, and 4G, the NQuire 1500 Mobula II ensures seamless communication.

High-Precision Barcode Scanning

At the core of the NQuire 1500 Mobula II lies Newland's advanced Megapixel scanning technology, ensuring efficient barcode data capture. This technology sets high standards for scanning both large and small 1D & 2D barcodes with precision. Moreover, the NQuire 1500 Mobula II is optimized for reading barcodes displayed on smartphone and tablet screens, enhancing its usability across various devices.

Flexible Mounting Landscape and Portrait

The NQuire 1500 Mobula II provides versatile mounting possibilities for both landscape and portrait orientations. Users have the flexibility to choose the position of the barcode reader and the back-lit Newland logo to suit the chosen orientation. With the classic Vesa75 configuration, seamless integration with established industry-standard solutions is guaranteed, simplifying the overall setup process.

Maximising Possibilities with NFC and MSR

The NQuire 1500 Mobula II has optional accessories for more connection and data capture, including an NFC module for contactless identification, secure access, or payment. The NQuire 1500 Mobula II also offers an MSR module to accommodate legacy applications.

Free Device Management Software

The NQuire 1500 Mobula II comes with Newland's free MDM solution: Ndevor. This software facilitates the management of information from a shared database, the arrangement of applications and settings across individual device units, and provides convenient troubleshooting assistance — all from a centralized location.

NQuire 1500 Mobula II

Data Capture

1D	All major 1D symbologies
2D	All major 2D symbologies
Depth of Field Code 39 (5mil)	110 mm - 290 mm
Depth of Field DataMatrix (10mil)	110 mm - 260 mm
Depth of Field EAN 13 (13mil)	70 mm - 610 mm
Depth of Field PDF417 (6.7mil)	110 mm - 230 mm
Depth of Field QR (15mil)	55 mm - 410 mm

Performance

Current Operating System	Android 13, GMS
Memory Flash	64GB
Memory RAM	4GB
Processor	2.0 GHz octa-core, 64-bit

Physical

AC Adapter	12 V, 3 A
Buttons	Up/down keys, Vol+/Vol-keys, Menu key
Dimensions	380.5(W) x 246.5(D) x 33(H) mm
Display	15.6"(1920 x 1080), brightness: 200 nits
Front camera	8 MP
Interfaces	USB-C, USB-A, Ethernet, GPIO, MicroSD Card
Keypad	5 keys
Modules	Built in 4G module
Notifications	Speaker, Multi-color LEDs
Power over Ethernet	RJ45 IEEE 802.3 af/at
Sensors	Gravity Sensor, Infrared sensor
SIM/TF	Nano+Nano, Nano+TF
Touch Panel	Capacitive touchscreen

Wireless

GPS	Beidou, GLONASS, Galileo, GPS (AGPS)
NFC	13.56MHz RFID: ISO14443A/B, MIFARE, FeliCa, NFC Forum Tags, ISO15693. Supports ID card reading, supports reader/writer modes. (optional NFC module is required)
WPAN RADIO	Bluetooth 5.2
WWAN RADIO	2G: 850/900/1800/1900MHz; 3G: WCDMA (B1, B2, 85, B8); CDMA: 1X EVDO (BC0); TD-SCDMA: B34/39; 4G: TDD-LTE (B34, B38, B39, B40, 841), FDD-LTE (B1, B2, B3, B5, B7, B8, B20, B28 a&b)

Environmental

Electro Static Discharge (ESD)	±12 kV (air discharge), ±6 kV (direct discharge)
Humidity	5% to 95% (non-condensing)

IP Rating	IP54 (front only)
Operating Temperature	-10°C to 50°C (14°F to 122°F)
Storage Temperature	-20°C to 60°C (-4°F to 140°F)

Software

Configuration Tools	Ndevor
MDM (certified)	Ndevor

Warranty

Comprehensive Service Contract	3 Years, 5 Years
Warranty Extension	+1 Year, +3 Years
Warranty Standard	2 Years

Accessories

Accessories Optional	Multiplug adapter, Desktop stand Vesa75, Wall mount bracket Vesa75, MSR reader module, NFC reader module, NQquire IO Kit
Accessories Standard	Multiplug adapter, Wall mount bracket Vesa75

What's in the box?

All versions	NQquire 1500 Mobula II, Wall mount bracket, Multiplug adapter
--------------	---

Accessories

Charging/Power

ADP0043 Power Supply for NQquire Series (ADP0043)

Peripherals

NLS-NQIOKIT-01 NQquire IO Kit (NLS-NQIOKIT-01)
 NLS-NQMSR-01 MSR Reader Module for NQquire Series (NLS-NQMSR-01)
 NLS-NQNFC-01 NFC Reader Module for NQquire Series (NLS-NQNFC-01)

Base Stations

STD1500 Foldable Desktop/Counter Stand for NQ1500 (STD1500)
 WMB750 Wall Mount Bracket for NQquire Series (WMB750)



Newland AIDC EMEA

Feel free to contact us or a partner near you.
info@newland-id.com - newland-id.com

Specifications are subject to change without notice
 © Newland AIDC EMEA 2026 - All rights reserved