



N1-ER

Scan Engines

 1D & 2D	 Chip	 CMOS	 Dual Interface	 EasySet	 Laser aimer
 Power consumption	 Standard	 Warranty 2 Years			



Features

6th Generation UIMG technology.

The N1-ER is armed with Newland's 6th generation UIMG scanning technology. Refined design, optimized accuracy, and increased speed, even on poor quality 1D and 2D barcodes are now at your fingertips.

Extended Scan Range.

The N1-ER adjusts the focus to capture codes from a greater distance than standard scanning. It is perfect for scanning high racks in the warehouse or codes on items loaded onto high-based transport vehicles without having to climb aboard. You can also integrate N1-ER into devices so that vehicle operators can remain seated when scanning box and pallet labels. The extra distance is supported by the bright laser aiming dot to help the users line up the correct code.

On-Screen Barcode Capture.

Newland continues their excellent track record and pioneering outlook to scanning barcodes displayed on-screen with the N1-ER. Whether the applications are at an extended range, or when screens are covered with protective film or set to their lowest brightness level, on-screen barcode scanning is no challenge for this engine.

Compact Design.

By decoding via an embedded chip instead of a separate processor, we've packed great depth of field, fast scanning and aiming technology into an incredibly small device. At only 23.8 x 10.5 x 7mm, it's ideal for integration into devices where space is a premium or if the design warrants a more inconspicuous scanner presence.

Outstanding Power Efficiency.

The N1-ER aims, illuminates and decodes barcodes while drawing as little current from the host device as possible. It prolongs battery life compared to like-for-like scanners, as well as offers an eco-conscious solution.

Multiple Interfaces.

Supporting both USB and TTL-232 interfaces the N1-ER gives integrators the choice between serial communication's tried and tested stability or USB's more dynamic data transmission rates.

2 Years Full
Warranty

 **EasySet**

TECHNICAL SPECIFICATIONS

N1-ER

Data Capture

1D	All major 1D symbologies, including Code 128, EAN-13, EAN-8, Code 39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5, ITF-6, ITF-14, ISBN, ISSN, Code 93, UCC/EAN-128, GS1 Databar, Matrix 2 of 5, Code 11, Industrial 2 of 5, Standard 2 of 5, AIM128, Plessey, MSI-Plessey.
2D	All major 2D symbologies, including PDF417, QR Code, Micro QR, Data Matrix, Aztec.

Aiming	Laser diode (650nm)
Depth of Field Code 128 (40mil)	115 mm - 1400 mm
Depth of Field Code 39 (20mil)	65 mm - 800 mm
Depth of Field Code 39 (5mil)	120 mm - 260 mm
Depth of Field EAN 13 (13mil)	105 mm - 680 mm
Depth of Field QR (15mil)	80 mm - 250 mm
Field of View Horizontal	28°
Field of View Vertical	21°
Illumination	White LED
Image Sensor	640 x 480 CMOS
Minimal Print Contrast	20%
Resolution	≥3mil (1D), ≥6.67mil (2D)
Scan Angle Pitch	±60°
Scan Angle Roll	360°
Scan Angle Skew	±60°

Performance

Decoder	ASIC (0610)
---------	-------------

Physical

Current @ 3.3VDC Operating	176 mA (typical)
Current @ 3.3VDC Standby	11.8 mA
Dimensions	23.8(W) x 10.5(D) x 7(H) mm (max)
Input Voltage	3.3 VDC ±5%
Interfaces	USB, TTL-232
Power Consumption	581 mW (typical)
Weight	2 g

Environmental

Ambient Light	0 to 100,000 lux (natural light)
Humidity	5% to 95% (non-condensing)
Operating Temperature	-20°C to 60°C (-4°F to 140°F)
Storage Temperature	-40°C to 70°C (-40°F to 158°F)

Software

Configuration Tools	EasySet
---------------------	---------

Certifications

Certifications Hardware	CE EMC Class B, FCC Part 15 Class B, RoHS
-------------------------	---

Warranty

Warranty Standard	2 Years
-------------------	---------

Accessories

Accessories Optional	USB cable, RS-232 cable, Software development board
----------------------	---

Accessories

Cables

FPC75mm Flat Printed Circuit Cable (FPC75mm)



Newland AIDC EMEA

Feel free to contact us or a partner near you.

info@newland-id.com - newland-id.com

Specifications are subject to change without notice

© Newland AIDC EMEA 2026 - All rights reserved