



NLS-WCD10-1C Charging Cradle for WD1

Base Stations

Features

Professional and Reliable Design.

The cradle has a simple and reliable design, which helps to fit the WD1 Wearable Scanner perfectly into the charging slot. The cradle ensures that WD1 is in good contact and stable charging.

Simultaneous Charging for Multi-terminals.

Each cradle can support one WD1 charging at the same time. A maximum of five cradles can be linked.

1 Year Full
Warranty

TECHNICAL SPECIFICATIONS

NLS-WCD10-1C Charging Cradle for WD1

Physical

AC Adapter	DC 19V 3.2A for spliced cradles
Dimensions	90(L)*70(W)*37(H) mm
Expected Charge Time	WD1≤3.5H (DC 19V 3.2A)
Notifications	LED
Weight	170g

Environmental

Drop	1.0m drops to concrete (for six sides, one drop per side)
Electro Static Discharge (ESD)	±8 kV (direct discharge), ±12 kV (air discharge)
Humidity	5% to 95% (non-condensing)
IP Rating	IP30
Operating Temperature	5°C to 45°C (-32°F to 113°F)
Storage Temperature	-30°C to 60°C (-22°F to 140°F)

Warranty

Warranty Standard	1 Year
-------------------	--------



Newland AIDC EMEA

Feel free to contact us or a partner near you.
info@newland-id.com - newland-id.com

Specifications are subject to change without notice
© Newland AIDC EMEA 2026 - All rights reserved