











FR21 Neon

Presentation Scanners

- 
1.2m drop
- 
1D & 2D
- 
CMOS
- 
Dual Interface
- 
EasySet
- 
IP50
- 
Mobile Reading
- 
Warranty
5 Years



Features

Customer-facing scanning solution.

First time, every time scanning of 1D and 2D barcodes from an LCD screen. The FR21 Neon was built to create an optimal customer experience at the POS. It scans quickly and easily, even for the most inexperienced user, making it an ideal solution for applications like Mobile Payment, Customer Loyalty and Ticket Verification.

Suits your POS perfectly.

The FR21 Neon is designed as a modern and attractive device that you can fully adjust to your brand and POS. Its compact size makes it ideal for positioning on a small desk, a store shelf or at the counter, where space is crucial. For added flexibility, the scanning head can be tilted up to 35° to accommodate objects of various shapes and sizes.

Subtle, modest illumination.

The FR21 Neon is equipped with a subtle, white light that optimizes the scanning performance without drawing unnecessary attention when faced outwards. Additionally, the depth of field helps customers scan quickly without causing the device to light up unnecessarily.

Customize for your brand.

It is easy and affordable to match the FR21 Neon to your brand. The fully flat front lends itself to simple cover designs and the round window (diameter 2.8 cm) underneath the scanner has LED lighting behind it, providing extra visibility for a company logo placed over it. This allows you to customize and change up the look of the device, even for small quantities. For large order quantities, the color of the full desktop scanner can be adjusted for further customization.

5 Years Full Warranty



TECHNICAL SPECIFICATIONS

FR21 Neon

Data Capture

1D	All major 1D symbologies, including Code 128, EAN-13, EAN-8, Code 39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5, ITF-6, ITF-14, ISBN, Code 93, UCC/EAN-128, GS1 Databar, Matrix 2 of 5, Code 11, Industrial 2 of 5, Standard 2 of 5, Plessey, MSI-Plessey.
2D	All major 2D symbologies, including PDF417, QR Code (QR1/2, Micro), Data Matrix (ECC200, ECC000, 050, 080, 100, 140), Chinese Sensible Code.
Field of View Horizontal	73°
Field of View Vertical	56°
Illumination	White LED

Image Sensor	640 x 480 CMOS
Minimal Print Contrast	25%
Scan Angle Pitch	±30°
Scan Angle Roll	360°
Scan Angle Skew	±30°
Scan Modes	Sense Mode, Continuous Mode
Scan Rate	60 frames per second

Performance

Processor	0390 Chip, MCU
-----------	----------------

Physical

Current @ 5VDC Operating	127.3 mA (typical), 280.7 mA (max)
Dimensions	70.5(W) × 60.2(D) × 120.7(H) mm
Housing	ABS
Input Voltage	5 VDC ±5%
Interfaces	USB, RS-232
Notifications	Beep
Power Supply Input	5 VDC (1.5 A)
Power Supply Output	AC100 to 240 V (50 to 60 Hz)
Weight	242 g

Environmental

Drop	1.2 m
Electro Static Discharge (ESD)	±12 kV (air discharge), ±6 kV (direct discharge)
Humidity	5% to 95% (non-condensing)
IP Rating	IP50
Operating Temperature	-20°C to 60°C (-4°F to 140°F)
Storage Temperature	-40°C to 70°C (-40°F to 158°F)

Software

Configuration Tools	EasySet
---------------------	---------

Certifications

Certifications Hardware	CE EMC Class B, FCC Part15 Class B
-------------------------	------------------------------------

Warranty

Warranty Standard	5 Years
-------------------	---------

Accessories

Accessories Optional	RS-232 cable, Adapter
Accessories Standard	USB cable



Newland AIDC EMEA

Feel free to contact us or a partner near you.
info@newland-id.com - newland-id.com

Specifications are subject to change without notice
© Newland AIDC EMEA 2026 - All rights reserved