















HT35 Leo II

Mobile Computer

-  1.5m drop
-  1D & 2D
-  4.0" screen
-  4G
-  Android 11
-  Bluetooth 5.0
-  Camera
-  GPRS
-  IP65
-  Laser aimer
-  Megapixel
-  Micro SD
-  NFC
-  Touchscreen
-  USB-C
-  Warranty 2 Years
-  WIFI Dual Band



Features

Supports.
1D and 2D barcodes.

Software.
Built on Android 11.

Display.
4 inch (480*800) high-definition capacitive touchscreen.

Processor.
Octa core 2.0GHz CPU.

Memory.
3GB RAM and 32GB ROM memory.

Offers.
Wi-Fi 802.11 a/b/g/n (2.4GHz & 5GHz), Bluetooth 5.0, camera, NFC, GSM, WCDMA.

2 Years Full Warranty

TECHNICAL SPECIFICATIONS

HT35 Leo II

Datenerfassung

1D	All major 1D symbologies
2D	All major 2D symbologies

Scanleistung

Aktuelles Betriebssystem	Android 11
Speicher-Flash	32GB
Speicher-RAM	3GB

Speichererweiterung (max.)	Micro SD card slot up to 256GB
Prozessor	2.2 GHz octa-core
Physikalisch	
Audio	Zwei Stereolautsprecher vorne, Lautstärke 90 dB ± 3 dB (Messabstand 10 cm)
Batterietyp	7.4 V, 19.24 Wh
Tasten	Power, scan keys, volume +/-
Abmessungen (mm)	196.4(W) x 74.8(D) x 26.8(H) mm
Anzeige	4" (800 x 480), IPS highlight screen
Erweiterungssteckplatz	Micro SD card slot up to 256GB
Erwartete Ladezeit	PE fast charging, full charge time < 4h
Schnittstellen	Federstifte, USB-C, OTG
Tastenfeld	40 Tasten
Benachrichtigungen	LED, Vibration, Ton
Sensoren	Proximity sensor, Acceleration sensor, Light sensor
SIM/TF	Nano SIM card slot *2
Touchpanel	5-Punkt-Kapazitiv-Touchscreen
Gewicht	350 g (including battery)

Kabellos

GPS	GPS, BD, GLONASS
WLAN RADIO	IEEE 802.11 a/b/g/n/ac 2.4G/5G dual band; supports fast roaming
WPAN RADIO	Bluetooth 5.0 BLE
WWAN RADIO	FDD LTE B1/B3/B5/B7/B8; TDD LTE B38/B39/B40/B41; WCDMA B1/B2/B5/B8; GSM B2/B3/B5/B8; CDMA1x/CDMA2000 BC0/BC1

Umwelt

Fallhöhe	1.5 meter drop to marble
Elektrostatische Entladung (ESD)	±8 kV (Kontaktentladung), ±16 kV (Luftentladung)
Feuchtigkeit	5 % bis 95 % (nicht kondensierend)
IP-Bewertung	IP65
Betriebstemperatur	-20 °C bis 55 °C (-4 °F bis 131 °F)
Lagertemperatur	-30 °C bis 70 °C (-22 °F bis 158 °F)

Zertifizierungen

Zertifizierungen Hardware	FCC, CCC, CTA, CE
---------------------------	-------------------

Garantie

Standardgarantie	2 Jahre
------------------	---------



Newland AIDC EMEA

Feel free to contact us or a partner near you.
info@newland-id.com - newland-id.com

Specifications are subject to change without notice
 © Newland AIDC EMEA 2026 - All rights reserved