


















# NQquire 350 Skate

Touch-Panel-PCs

					
1D & 2D	4.3" screen	Android 7.1	Bluetooth 4.0	CMOS	I/O Ctrl
					
Megapixel	Micro SD	Ndevor	PoE	RFID	Touchscreen
					
USB	Warranty 2 Years	WiFi			



## Features

### Self-Scanning focused.

The NQquire 350 Skate is armed with a 2D omni-directional scan engine. Its megapixel scanner easily reads barcodes, no matter the size or material that it's been printed on. A 20 degree angle of the reader makes scanning larger products comfortable. For digital barcodes, this same tilt guides each user to present their smart phone at the optimal angle to combat reflection.

### Heavily customized Android OS for easy integration and Device Management.

Running on Android 7.1, the NQquire 350 Skate ensures intuitive navigation to your customers and your team. Looking up product information, scanning tickets or checking prices is quick and simple. Meanwhile software and development possibilities are as powerful and widespread as they are in larger equivalents.

### Greater visibility.

Newland's MDM Ndevor, included with each NQquire 350 Skate, makes updating and maintaining devices even easier by connecting them to a cloud-based configuration and monitoring tool.

### Endless communication possibilities.

The NQquire 350 Skate is equipped with a variety of features that make it easy to adapt the micro kiosk to your application. The device has a built-in RFID reader and data can be transmitted through Ethernet, WiFi and Bluetooth. An external USB and GPIO port provides the possibility to connect an external device, such as a handheld scanner.

### Mount anywhere.

With its small footprint and VESA 75 compliant design, the NQquire 350 Skate can be mounted on any shelf, pole or wall.

### Backwards compatible.

The NQquire 350 Skate's embedded CIT emulation program means the device can emulate the exact functions of the NQquire 200 series. Enabling prior customers to explore what's possible with Android while they continue their existing processes.

**2 Years Full Warranty**

**Ndevor**  
NEWLAND SOFTWARE

## TECHNICAL SPECIFICATIONS

# NQquire 350 Skate

### Datenerfassung

1D	All major 1D symbologies
----	--------------------------

2D	All major 2D symbologies
Zielen	Laserdiode (625 ± 10 nm)
Beleuchtung	Weißer LED (625±10 nm)
Bildsensor	1280 x 800 CMOS
Scan-Modi	Sensor-Modus
Scanrate	60 frames per second

### Scanleistung

Aktuelles Betriebssystem	Android 7.1
Speicher-Flash	8GB
Speicher-RAM	2GB
Speichererweiterung (max.)	Micro SD up to 128GB
Prozessor	1.5 GHz octa-core

### Physikalisch

Audio	88 dB (850 Hz bis 20 kHz) Zweikanal-Stereoklang
Abmessungen (mm)	140(W) x 139.5(D) x 61(H) mm
Anzeige	4,3" (480 x 272) TFT LCD Display
Erweiterungssteckplatz	Micro SD up to 128GB
Schnittstellen	USB 2.0, GPIO
Stromverbrauch	6 W
Strom über Ethernet	802.3 af
Netzteil Eingang	AC 110 to 220 V (50 to 60 Hz)
Netzteil Ausgang	DC12 V, 2 A
Touchpanel	Kapazitiv-Touchscreen
VESA-Standard	Complies with standard 75 bracket, enabling easy mounting on shelves and walls
Gewicht	403 g

### Kabellos

RFID	ISO/IEC 14443 A/B ISO/IEC 15693; MIFARE 1K/4K; MIFARE DESFire; Sony FeliCa
WLAN RADIO	IEEE 802.11a/b/g/n/ac
WPAN RADIO	Bluetooth 4.0 LE

### Umwelt

Feuchtigkeit	Betrieb: 5 % bis 90 % (nicht kondensierend), Lager: 5 % bis 95 % (nicht kondensierend)
Betriebstemperatur	-10 °C bis 50 °C (14 °F bis 122 °F)
Lagertemperatur	-20 °C bis 60 °C (-4 °F bis 140 °F)

### Software

Konfigurationstools	Ndevor
MDM (zertifiziert)	Ndevor, SOTI

### Garantie

Standardgarantie	2 Jahre
------------------	---------



**Newland AIDC EMEA**

Feel free to contact us or a partner near you.

[info@newland-id.com](mailto:info@newland-id.com) - [newland-id.com](http://newland-id.com)

Specifications are subject to change without notice

© Newland AIDC EMEA 2026 - All rights reserved