



DC850 Susu 2D

Mobile Computer

		2,300 mAh			LINUX
1.2m drop	1D & 2D		CMOS	IP54	LINUX



Warranty
2 Years

Features

Inventory Management Software.

The DC850 Susu 2D comes equipped with powerful, easy to use, inventory management software. With this combination of software and hardware, it is easy to efficiently manage your inventory flow

Extended Battery Life.

Enabling you to get through the entire workday, the battery of the DC850 Susu 2D lasts up to 26 hours per charge.

Functional Design.

With a design that is focused on the user, the DC850 Susu 2D is lightweight and well balanced in order to reduce stress and fatigue during long working hours.

Rugged Construction.

The DC850 Susu 2D has a housing built for rough environments with an IP54 sealing and 1.2m drop rating.

Price vs Performance.

As well as excellent performance, the DC850 Susu 2D is a durable scanning solution at a price that is suitable for your budget.

2 Years Full
Warranty

TECHNICAL SPECIFICATIONS

DC850 Susu 2D

Datenerfassung

1D	All major 1D symbologies, including Code128, EAN EAN-13, EAN EAN-8, Code Code-39, UP UPC-A, UPC UPC-E, Codabar, ISBN/ISSN, Interleaved 2 of 5, Code 93.
2D	All major 2D symbologies, including PDF -417, QR Code, Data Matrix, Maxicode, Aztec.

Scanleistung

Aktuelles Betriebssystem	Linux
Speicher-Flash	128MB
Speicher-RAM	32MB

Prozessor 1.0 GHz

Physikalisch

Batterietyp	3.7 V, 2300 mAh, Rechargeable lithium polymer battery
Abmessungen (mm)	168.5(W) x 65(D) x 39.5(H) mm
Anzeige	Level 8 monochrome display with resolution 160x160
Erwartete Akkulaufzeit	26 hours
Schnittstellen	USB
Tastensfeld	26 Tasten
Benachrichtigungen	Lautsprecher, Mehrfarbige LEDs
Netzteil Eingang	AC 100 to 240 V (50 to 60 Hz)
Netzteil Ausgang	DC5 V, 1.5 A
Gewicht	270 g (including battery)

Umwelt

Fallhöhe	1.2 m
Elektrostatische Entladung (ESD)	±8 kV (direkte Entladung), ±12 kV (Luftentladung)
Feuchtigkeit	5 % bis 95 % (nicht kondensierend)
IP-Bewertung	IP54
Betriebstemperatur	-10 °C bis 50 °C (14 °F bis 122 °F)
Lagertemperatur	-20 °C bis 60 °C (-4 °F bis 140 °F)

Garantie

Standardgarantie	2 Jahre
------------------	---------

Zubehör

Optionales Zubehör	USB-Kabel, Akku, Netzteil
--------------------	---------------------------

Newland AIDC EMEA

Feel free to contact us or a partner near you.

info@newland-id.com - newland-id.com

Specifications are subject to change without notice

© Newland AIDC EMEA 2026 - All rights reserved