



# SD35 Leo

## Mobile Computer

-  1.5m drop
-  1D & 2D
-  3.5" screen
-  4G
-  5,200 mAh
-  Android 8.1
-  Bluetooth 4.1
-  Camera
-  GPRS
-  IP65
-  Laser aimer
-  Location
-  Megapixel
-  Micro SD
-  NFC
-  Touchscreen
-  USB-C
-  Warranty 2 Years
-  WIFI Dual Band



## Features

**Supports.**  
1D and 2D barcodes

**Software.**  
Built on Android 8.1

**Display.**  
3.5 inch (640 x 960) high-definition screen

**Processor.**  
Octa core 2.0GHz CPU

**Memory.**  
2GB RAM and 16GB ROM memory

**Offers.**  
Wi-Fi 802.11 a/b/g/n (2.4GHz & 5GHz), Bluetooth 4.1, camera, NFC, GSM, WCDMA

**2 Years Full Warranty**

### TECHNICAL SPECIFICATIONS

## SD35 Leo

### Datenerfassung

1D	Auspost, Bpo, Canpost, Codabar, Code11, Code128, Code32, Code39, Code93, Dutchpost, Ean13, Ean8, Ean128, Int25, Isbt, Iata25, Japost, Msi, Ocr, Planet, Postnet, Strt25, Tlc39, Trioptic, Upca, and Upce
2D	Aztec, Codablock, Code49, Composite, Datamatrix, Maxicode, Micropdf, Pdf417, Qr, and Rss

## Scanleistung

Aktuelles Betriebssystem	Android 8.1
Speicher-Flash	16GB
Speicher-RAM	2GB
Prozessor	2.0 GHz octa-core

## Physikalisch

Audio	Zwei Stereolautsprecher vorne, Lautstärke 90 dB ± 3 dB (Messabstand 10 cm)
Batterietyp	5200 mAh
Tasten	Keyboard, volume buttons, power button, unction buttons (left and right)
Abmessungen (mm)	184(W) x 70(D) x 29.8(H) mm
Anzeige	3.5" (640 x 960), IPS highlight screen
Erweiterungssteckplatz	1 Micro PSAM and 1 Micro SD card up to 128 GB
Erwartete Ladezeit	PE fast charging, full charge time < 4h
Schnittstellen	USB-C, OTG
Tastenfeld	40 Tasten
Benachrichtigungen	LED, Vibration, Ton
Rückkamera	13 MP, Autofokus, LED-Blitz mit hoher Leuchtkraft
SIM/TF	2 Micro SIM
Touchpanel	5-Punkt-Kapazitiv-Touchscreen
Gewicht	290 g (with battery)

## Kabellos

GPS	GPS, BD, GLONASS
NFC	ISO1443A/B, ISO15693, NFC reading distance: 0 to 5cm
WLAN RADIO	IEEE 802.11 a/b/g/n 2.4G 5G dual frequency
WPAN RADIO	Bluetooth 4.1 BLE
WWAN RADIO	FDD-LTE B1/B3/B7 TDD-LTE B38/B39/B40/B41 TDSCDMA B34/B39 WCDMA B1/B2/B5/B8 CDMA1x/CDMA2000 BC0

## Umwelt

Fallhöhe	6 sides can withstand the impact of 1.5 meters drop to concrete
Elektrostatische Entladung (ESD)	±8 kV (Kontaktentladung), ±16 kV (Luftentladung)
Feuchtigkeit	5 % bis 95 %
IP-Bewertung	IP65
Betriebstemperatur	-20 °C bis 60 °C (-4 °F bis 140 °F)
Lagertemperatur	-30 °C bis 80 °C (-22 °F bis 176 °F)

## Zertifizierungen

Zertifizierungen Hardware	FCC, CCC, CTA, CE
---------------------------	-------------------

## Garantie

Standardgarantie	2 Jahre
------------------	---------



**Newland AIDC EMEA**

Feel free to contact us or a partner near you.

[info@newland-id.com](mailto:info@newland-id.com) - [newland-id.com](http://newland-id.com)

Specifications are subject to change without notice

© Newland AIDC EMEA 2026 - All rights reserved