



# NLS-WCD10-1C Charging Cradle for WD1

Sockel und Halterungen

## Features

### Professional and Reliable Design.

The cradle has a simple and reliable design, which helps to fit the WD1 Wearable Scanner perfectly into the charging slot. The cradle ensures that WD1 is in good contact and stable charging.

### Simultaneous Charging for Multi-terminals.

Each cradle can support one WD1 charging at the same time. A maximum of five cradles can be linked.

**1** Year Full  
Warranty

## TECHNICAL SPECIFICATIONS

### NLS-WCD10-1C Charging Cradle for WD1

#### Physikalisch

AC Adapter	DC 19V 3.2A for spliced cradles
Abmessungen (mm)	90(L)*70(W)*37(H) mm
Erwartete Ladezeit	WD1≤3.5H (DC 19V 3.2A)
Benachrichtigungen	LED
Gewicht	170g

#### Umwelt

Fallhöhe	1.0m drops to concrete (for six sides, one drop per side)
Elektrostatische Entladung (ESD)	±8 kV (direkte Entladung), ±12 kV (Luftentladung)
Feuchtigkeit	5 % bis 95 % (nicht kondensierend)
IP-Bewertung	IP30
Betriebstemperatur	5 °C bis 45 °C (-32 °F bis 113 °F)
Lagertemperatur	-30 °C bis 60 °C (-22 °F bis 140 °F)

#### Garantie

Standardgarantie	1 Jahr
------------------	--------



**Newland AIDC EMEA**

Feel free to contact us or a partner near you.

[info@newland-id.com](mailto:info@newland-id.com) - [newland-id.com](http://newland-id.com)

Specifications are subject to change without notice

© Newland AIDC EMEA 2026 - All rights reserved