





















MT95 Kambur Pro

Terminales portátiles

					
1.5m drop	1D & 2D	5G	6,000 mAh	6.1" screen	Acuscan
					
Android 11	Bluetooth 5.2	GMS	GPS	IP67	Megapixel
					
Ndevor	NFC	Touchscreen	USB-C	Warranty 2 Years	WiFi Dual Band

Features

Dual 5G SIM Slots.

The MT95 Kambur Pro features 5G network connectivity, adding greater speed, lower latency, and larger capacity to transfer business-critical data. Featuring two nano SIM card slots, the MT95 Kambur Pro allows the customer to add separate voice and data. Moreover, the additional SIM provides the end-user with an extra way to reduce the risks of downtime.

Powerful Performance.

The MT95 Kambur Pro comes with an Android 11 GMS operating system and is powered by a 2.2GHz octa-core processor. The 6GB RAM and 128GB flash memory further support the device's outstanding performance in handling applications and filing data.

Megapixel Scanning.

The MT95 Kambur Pro has Newland Megapixel 2D scanning technology for high-performance scanning of 1D and 2D barcodes, even if they are damaged or distorted. The laser aiming uses the Acuscan feature to ensure the user can decode barcodes even when they are displayed closely together.

Large Battery Capacity and Super-Fast Charging.

Equipped with a 6000mAh battery, the MT95 Kambur Pro is supplemented by a low-power design, significantly extending the device's usage time. Besides, it supports fast charging with a Type-C port and charging power up to 18W.

Full Wireless Features.

In addition to 5G, the MT95 Kambur Pro has various other wireless options, including dual-band WiFi, the latest Bluetooth 5.2, GPS, and NFC. Whether inside or outside a local area network, the MT95 Kambur Pro maintains communication with its host application while peripheral devices stay connected to it.

Device Management & Software Tools.

The MT95 Kambur Pro comes fully equipped with Newland's free Ndevor MDM for managing all your devices from one location. SOTI, AirWatch, and 42 Gears are alternative MDM options for the MT95 Kambur Pro.

2 Years Full Warranty



TECHNICAL SPECIFICATIONS

MT95 Kambur Pro

Captura de datos

1D	All major 1D symbologies	MT95 Kambur Pro Page 1 of 3
----	--------------------------	-------------------------------

2D	All major 2D symbologies
Puntero	Diodo láser
Profundidad de campo Code 39 (5mil)	120 mm - 280 mm
Profundidad de campo Data Matrix (10mil)	110 mm - 260 mm
Profundidad de campo EAN 13 (13 mil)	70 mm - 600 mm
Profundidad de campo PDF417 (6.7mil)	110 mm - 230 mm
Profundidad de campo QR (15mil)	55 mm - 400 mm
Iluminación	LED blanco (625±10 nm)
Sensor de imagen	1280 x 800 CMOS
Modos de escaneado	Modo de disparo
Velocidad de lectura	60 frames per second

Rendimiento

Sistema operativo actual	Android 11, GMS
Memoria flash	128GB
Memoria RAM	6GB
Procesador	2.2 GHz octa-core, 64-bit

Físico

Adaptador CA	18 W fast charging supported
Tipo de batería	3.85 V, 6000 mAh, Smart battery
Dimensiones (mm)	165(W) × 78.5(D) × 15.5(H) mm
Pantalla	6.1" (1560 x 720), 500 Nits
Cámara frontal	8 MP, Enfoque fijo
Interfaces	USB-C, OTG
Teclado	5 teclas
Notificaciones	Altavoz, Vibración, LED multicolor
Cámara trasera	13 MP, Flash LED, Enfoque automático
Sensores	G-sensor, Magnetic sensor, Light & proximity sensor, Acceleration sensor
SIM/TF	2 Nano SIM card slots
Panel táctil	Gorilla Glass
Peso	287 g (including battery)

Inalámbrico

GPS	GLONASS, Galileo, GPS (AGPS)
RFID	13.56MHz ISO14443A/B, ISO15693, ISO18000-3, MIFARE, FeliCa RF, Kovio, NFC Forum Type 1-4 Tags
RADIO WLAN	built-in 802.11 a/b/g/n/ac, support 2.4G and 5G dual frequency
RADIO WPAN	Bluetooth 5.2 BLE
RADIO WWAN	2G: GSM (B2, B3, B5, B8); 3G: WCDMA (B1, B2, B5, B8); CDMA: 1X EVDO (BC0); 4G: TDD-LTE (B34, B38, B39, B40, B41) FDD-LTE (B1, B2, B3, B5, B7, B8, B20, B28 a&b); 5G: NR (N1/3/8/28/38/41/77/78/79)

Medioambiental

Caídas	1.5 m
--------	-------

Descarga electroestática (ESD)	±8 kV (descarga directa), ±15 kV (descarga en aire)
Humedad	5 % al 95 % (sin condensación)
Grado de protección IP	IP67
Temperatura de funcionamiento	De -20 °C a 50 °C (de -4 °F a 122 °F)
Temperatura de almacenamiento	De -30 °C a 60 °C (de -22 °F a 140 °F)

Software

Herramientas de configuración	Ndevor
MDM (certificado)	Ndevor

Garantía

Garantía estándar	2 años
-------------------	--------

Accesorios

Accesorios opcionales	Cable USB-C, Cargador de batería de 4 ranuras, Base de carga, Empuñadura de pistola, Funda protectora, Adaptador, Protector de pantalla, Funda, Correa de mano
Accesorios estándar	Cable USB, Correa de mano, Batería, Adaptador de CA

Newland AIDC EMEA

Feel free to contact us or a partner near you.

info@newland-id.com - newland-id.com

Specifications are subject to change without notice

© Newland AIDC EMEA 2026 - All rights reserved