



















SD60 Pegasus II

Terminales portátiles



-  1.2m drop
-  1D & 2D
-  4G
-  6" screen
-  6,000 mAh
-  Android 11
-  Bluetooth 5.0
-  Camera
-  GPRS
-  IP65
-  Laser aimer
-  Location
-  Megapixel
-  Micro SD
-  NFC
-  Touchscreen
-  USB-C
-  Warranty 2 Years


WIFI Dual Band

Features

Supports
1D and 2D barcodes.

Software.
Built on Android 11.

Display.
6.0 inch (2160 x 1080) 5 point capacitive touch screen.

Processor.
Octa core 2.0GHz CPU.

Offers.
Wi-Fi 802.11 a/b/g/n/ac (2.4GHz & 5GHz). Bluetooth 5.0, camera, GPS, NFC, GSM, WCDMA.

Accessories.
Supplied with cradle.

2 Years Full Warranty

TECHNICAL SPECIFICATIONS

SD60 Pegasus II

Captura de datos

1D	Auspost, Bpo, Canpost, Codabar, Code11, Code128, Code32, Code39, Code93, Dutchpost, Ean13, Ean8, Ean128, Int25, Isbt, Iata25, Japost, Msi, Ocr, Planet, Postnet, Strt25, Tlc39, Trioptic, Upca, and Upce
2D	Aztec, Codablock, Code49, Composite, Datamatrix, Maxicode, Micropdf, Pdf417, Qr, and Rss

Rendimiento

Sistema operativo actual	Android 11
Memoria flash	64GB
Memoria RAM	4GB
Procesador	2.0 GHz octa-core

Físico

Audio	Altavoces estéreo frontales dobles, Volumen: 90 dB ± 3 dB (distancia de prueba: 10 cm)
Tipo de batería	6000 mAh
Botones	Volume keys, function keys (1 left, 1 right), power key
Dimensiones (mm)	160(W) x 80(D) x 15.8(H) mm
Pantalla	6.0" (2160 x 1080) IPS HD touch screen
Ranura de expansión	Micro SD card slot
Tiempo de carga previsto	PE fast charge, full charge time < 4h
Cámara frontal	5 MP
Interfaces	USB-C
Teclado	5 teclas
Notificaciones	LED, Vibración, Sonido
Cámara trasera	13 MP, Enfoque automático, Flash LED de alta intensidad
Sensores	G-sensor, Proximity sensor, COMPASS, Ambient light sensor
SIM/TF	2 Nano SIM card slots
Panel táctil	Pantalla táctil capacitiva de 5 puntos
Peso	300 g (with battery)

Inalámbrico

GPS	GPS, BD, GLONASS
NFC	ISO14443A/B, 15015693, NFC Reading distance: 0 to 5cm
RADIO WLAN	IEEE 802.11 a/b/g/n/ac 2.4G 5G dual frequency
RADIO WPAN	Bluetooth 5.0
RADIO WWAN	FDD-LTE B1/B3/B5/B7/B8, TDD-LTE B38/B39/B40/B41, TDSCDMA B34/B39, WCDMA B1/B2/B5/B8, GSM B2/B3/B5/B8, CDMA1x/CDMA2000 BC0/BC1

Medioambiental

Caídas	1.2 meters drop to concrete floor
Descarga electrostática (ESD)	±8 kV (descarga por contacto), ±15 kV (descarga en aire)
Humedad	5 % al 95 %
Grado de protección IP	IP65
Temperatura de funcionamiento	De -20 °C a 55 °C (de -4 °F a 131 °F)
Temperatura de almacenamiento	De -30 °C a 70 °C (de -22 °F a 158 °F)

Certificados

Certificaciones Hardware	CCC, CTA, CE
--------------------------	--------------

Garantía

Garantía estándar	2 años
-------------------	--------



Newland AIDC EMEA

Feel free to contact us or a partner near you.

info@newland-id.com - newland-id.com

Specifications are subject to change without notice

© Newland AIDC EMEA 2026 - All rights reserved