



NQuire 750 Stingray

Ordenadores con panel táctil

					
1D & 2D	4G	7" screen	Android 7.1	Bluetooth 4.0	Camera
					
I/O Ctrl	Megapixel	Micro SD	Ndevor	NFC	PoE
					
RFID	Touchscreen	USB	Warranty 2 Years	WiFi Dual Band	



Features

Android OS.

The NQuire 750 Stingray uses Android 7.1 OS. With this reliable operating system comes a feature-rich environment for stable apps that are tried and tested. Android 7.1 is an excellent match for the applications most suited to the NQuire 750. Particularly when operating within four walls, fitting the NQuire 750's PoE (Power over Ethernet) connectivity.

Free MDM included.

The NQuire 750 Stingray comes with the option of running Newland's free MDM solution: Ndevor. As a result, the Micro Kiosk lends itself perfectly for the coordination of multiple units. Managing information from a shared database, organizing applications and settings across many individual units, as well as low-touch assistance in troubleshooting can all be managed from a centralized location.

Mount anywhere.

The NQuire 750 Stingray's slimline and lightweight design is suitable for mounting on any shelf edge. Options to mount the NQuire series range from shelf to wall and free-standing. Its classic Vesa75 configuration also ensures existing industry standard, 3rd party solutions are compatible.

Snappy Megapixel Scanning.

Barcode data capture is at the heart of Newland's Micro Kiosks and so the NQuire 750 is fitted with their own Megapixel scanning technology. This maintains high standards for the scanning of both large and small 1D & 2D barcodes. The Micro Kiosk further includes optimal settings for reading barcodes presented on smartphone and tablet screens. With the scanner set at a 20° angle, it matches the ergonomics of how the user presents codes for scanning.

Multi-purpose display.

The sharp, full-colour screen on the Stingray is perfect for running animations and live recorded videos when not actively being used. With onboard memory, expanded memory and online options, the choice of content to display is virtually limitless.

Endless communication possibilities.

With WiFi, Ethernet, Powered Ethernet (PoE) and Bluetooth, this Micro Kiosk offers a variety of standard communication possibilities. Additionally, optional 4G means that the NQuire 750 Stingray can communicate and be communicated with, no matter the circumstance. Adding to that the wide variety of data capture options, such as integrated barcode reading, MSR, NFC and low frequency RFID, application possibilities are endless. Modules can only be ordered pre-mounted to the connector on the left or right side.

2 Years Full Warranty

Ndevor
NEWLAND SOFTWARE

NQuire 750 Stingray

Captura de datos

1D	All major 1D symbologies
2D	All major 2D symbologies
Puntero	Diodo láser (625 ± 10 nm)
Iluminación	LED blanco (625±10 nm)
Sensor de imagen	1280 x 800 CMOS
Modos de escaneado	Modo Sensorial
Velocidad de lectura	60 frames per second

Rendimiento

Sistema operativo actual	Android 7.1
Memoria flash	8 GB de eMMC
Memoria RAM	2GB DDR3
Expansión del almacenamiento de memoria (máx.)	Micro SD up to 128GB
Procesador	1.5 GHz octa-core, 64-bit

Físico

Audio	Sonido estéreo de dos canales a 82 dB
Dimensiones (mm)	195(W) x 138.5(D) x 25(H) mm
Pantalla	7" (1280 x 800) IPS display
Ranura de expansión	Micro SD up to 128GB
Cámara frontal	5 MP, Enfoque fijo
Tensión de entrada	12 V CC (2 A)
Interfaces	Micro USB 2.0, USB 2.0, GPIO, OTG
Consumo eléctrico	12 W (max)
Alimentación a través de Ethernet	RJ45 Ethernet, 10/100/1.000BASE-T
Entrada de fuente de alimentación	AC 110 to 220 V (50 to 60 Hz)
Salida de fuente de alimentación	DC12 V, 2 A
Sensores	Gravity Sensor
Panel táctil	Pantalla táctil capacitiva de 5 puntos
VESA estándar	Complies with the standard VESA 75 bracket, enabling easy mounting on shelves and walls

Inalámbrico

RFID	ISO/IEC 14443 A/B ISO/IEC 15693; MIFARE 1K/4K; MIFARE DESFire; Sony FeliCa (optional)
RADIO WLAN	IEEE 802.11 a/b/g/n/ac, 2.4GHz and 5Ghz (optional)
RADIO WPAN	Bluetooth 4.0 LE, EDR + BLE (optional)

Medioambiental

Humedad	5 % al 90 % (sin condensación)
Grado de protección IP	IP54 (solo en la parte delantera)
Temperatura de funcionamiento	De -10 °C a 50 °C (de 14 °F a 122 °F)

Temperatura de almacenamiento

De -20 °C a 60 °C (de -4 °F a 140 °F)

Software

Herramientas de configuración	Ndevor
MDM (certificado)	Ndevor, SOTI
Emulación de terminal	StayLinked, Airwatch

Certificados

Certificaciones Hardware	IEC 62471, RoHS, CE
--------------------------	---------------------

Garantía

Contrato de servicio integral	3 años, 5 años
Extensión de garantía	+1 año, +3 años
Garantía estándar	2 años

Accesorios

Accesorios opcionales	Adaptador múltiple de carga, Soporte de escritorio VESA 75, Soporte de montaje en pared VESA 75, Módulo lector MSR, Módulo lector NFC, Módulo 4G, Módulo lector RFID de baja frecuencia
Accesorios estándar	Adaptador múltiple de carga, Soporte de montaje en pared VESA 75

¿Qué incluye la caja?

NLS-NQUIRE751PRW-7C	NQuire 750 Stingray, Wall mount bracket, Multiplug adapter
---------------------	--

Accessories

Bases y soportes

STD1200 Desktop Stand for NQuire Series (STD1200)

WMB750 Wall Mount Bracket for NQuire Series (WMB750)



Newland AIDC EMEA

Feel free to contact us or a partner near you.

info@newland-id.com - newland-id.com

Specifications are subject to change without notice

© Newland AIDC EMEA 2026 - All rights reserved