



# DC850 Susu 2D

Terminales portátiles

		2,300 mAh			LINUX
1.2m drop	1D & 2D		CMOS	IP54	LINUX



Warranty  
2 Years

## Features

### Inventory Management Software.

The DC850 Susu 2D comes equipped with powerful, easy to use, inventory management software. With this combination of software and hardware, it is easy to efficiently manage your inventory flow

### Extended Battery Life.

Enabling you to get through the entire workday, the battery of the DC850 Susu 2D lasts up to 26 hours per charge.

### Functional Design.

With a design that is focused on the user, the DC850 Susu 2D is lightweight and well balanced in order to reduce stress and fatigue during long working hours.

### Rugged Construction.

The DC850 Susu 2D has a housing built for rough environments with an IP54 sealing and 1.2m drop rating.

### Price vs Performance.

As well as excellent performance, the DC850 Susu 2D is a durable scanning solution at a price that is suitable for your budget.

**2** Years Full  
Warranty

## TECHNICAL SPECIFICATIONS

### DC850 Susu 2D

#### Captura de datos

1D	All major 1D symbologies, including Code128, EAN EAN-13, EAN EAN-8, Code Code-39, UP UPC-A, UPC UPC-E, Codabar, ISBN/ISSN, Interleaved 2 of 5, Code 93.
2D	All major 2D symbologies, including PDF -417, QR Code, Data Matrix, Maxicode, Aztec.

#### Rendimiento

Sistema operativo actual	Linux
Memoria flash	128MB
Memoria RAM	32MB

Procesador 1.0 GHz

### Físico

Tipo de batería	3.7 V, 2300 mAh, Rechargeable lithium polymer battery
Dimensiones (mm)	168.5(W) x 65(D) x 39.5(H) mm
Pantalla	Level 8 monochrome display with resolution 160x160
Autonomía de la batería prevista	26 hours
Interfaces	USB
Teclado	26 teclas
Notificaciones	Altavoz, LED multicolor
Entrada de fuente de alimentación	AC 100 to 240 V (50 to 60 Hz)
Salida de fuente de alimentación	DC5 V, 1.5 A
Peso	270 g (including battery)

### Medioambiental

Caídas	1.2 m
Descarga electrostática (ESD)	±8 kV (descarga directa), ±12 kV (descarga en aire)
Humedad	5 % al 95 % (sin condensación)
Grado de protección IP	IP54
Temperatura de funcionamiento	De -10 °C a 50 °C (de 14 °F a 122 °F)
Temperatura de almacenamiento	De -20 °C a 60 °C (de -4 °F a 140 °F)

### Garantía

Garantía estándar	2 años
-------------------	--------

### Accesorios

Accesorios opcionales	Cable USB, Batería, Adaptador
-----------------------	-------------------------------



#### Newland AIDC EMEA

Feel free to contact us or a partner near you.

[info@newland-id.com](mailto:info@newland-id.com) - [newland-id.com](http://newland-id.com)

Specifications are subject to change without notice

© Newland AIDC EMEA 2026 - All rights reserved