



HR32 Marlin Bluetooth

Escáneres de mano

					
1.5m drop	1D & 2D	2,400 mAh	Bluetooth 5.0	Dual Interface	EasySet
					
IP52	Megapixel	Warranty 3 Years			

Features

Fantastic Megapixel scan technology.

Equipped with a megapixel barcode scanner, the HR32 Marlin Bluetooth reads virtually all 1D or 2D barcode with better reading performance on long or truncated 1D codes, larger and high-density 2D codes. Complicated stacked 2D barcodes codes for emerging applications in track and trace are no issue for the HR32 Bluetooth.

Reliable Wireless Connection.

Adopting the latest Bluetooth 5.0 technology, the HR32 Marlin Bluetooth is able to maintain a strong, anti-interference connection to transmit data. Achieving communication distances of up to 50m, the Marlin is as at home in a tight localized workspace where wires are unwanted clutter, as it is to bridging wider gaps from a host to a scanner.

Seven scanners to one base station.

The Bluetooth 5.0 technology selected for the HR32 Marlin Bluetooth allows up to 7 scanners to be paired to a single base station, allowing coordinated scanning applications to transmit data a single host. This maximises available human resource without having to match up each scanner with a different PC, tablet or mobile computer.

Real time and batch.

The intelligence in the HR32 Marlin Bluetooth allows the user to move seamlessly from direct BT download to a host. When out of range, it can store captured codes and download them when back in range. With its large memory capacity, enabling storage of up to 15,000 standard EAN barcodes, the Marlin can set up to work as a pure data collector.

Configurable Illumination

The HR32 Marlin Bluetooth uses a combination of red and white light that can be used in tandem or independently of one another via the comprehensive user manual or via the software configuration tools.

Powerful Data Editing.

The HR32 Marlin Bluetooth is compatible with Newland's EasySet configuration software, allowing users to create the ideal configurations to match the Marlin's incredible scanning performance with their application requirements. It has complex data formatting options to match the ever increasing complexities demanded from 2D barcodes in practical applications.

3 Years Full Warranty



TECHNICAL SPECIFICATIONS

HR32 Marlin Bluetooth

Captura de datos

1D	All major 1D symbologies, including EAN-8, EAN-13, UPC-E, UPC-A, Code128, Coupon, UCC/EAN128, CodaBar, I2Of5, Febraban, ITF14, ITF6, Matrix 25, Code39, Code93, ISSN, ISBN, Industrial 25, Standard 25, China Posy 25, Plessey, Code 11, MSI Plessey, UCC/EAN Composite, GS1 Databar, Code 49, Code 16K, AIM 128, ISBT 128.
----	---

2D All major 2D symbologies, including PDF417, MicroPDF417, QR Code, Micro QR Code, Aztec, Data Matrix, Chinese Sensible Code, Maxicode.

Puntero	LED verde
Profundidad de campo Code 39 (5mil)	85 mm - 220 mm
Profundidad de campo Data Matrix (10mil)	50 mm - 220 mm
Profundidad de campo EAN 13 (13 mil)	50 mm - 495 mm
Profundidad de campo PDF417 (6.67mil)	70 mm - 215 mm
Profundidad de campo QR (15mil)	20 mm - 325 mm
Campo de visión horizontal	39°
Campo de visión vertical	24°
Iluminación	White LED, LED rojo
Sensor de imagen	1280 x 800 CMOS
Contraste de impresión mínimo	25%
Inclinación del ángulo de escaneado	±55°
Balaceo del ángulo de escaneado	360°
Sesgo del ángulo de escaneado	±55°

Rendimiento

Memoria flash	≥15 000 unidades Código 128 (20 bytes por cada código 128)
---------------	--

Físico

Tipo de batería	2400 mAh lithium-ion battery
Dimensiones (mm)	113.5(W) x 73.3(D) x 159(H) mm
Autonomía de la batería prevista	≥12 hours of continuous operation (scan once per 6 seconds)
Tiempo de carga previsto	≤4 hours
Tensión de entrada	5 V CC ±5 %
Interfaces	USB, RS-232
Notificaciones	Pitido, LED
Peso	217 g

Inalámbrico

Modos de comunicación	Sincrónico, Asíncrono, Lote
Tecnología de radio	Bluetooth 5.0
Distancia inalámbrica (máx.)	≥50 m (direct line of sight in open air)

Medioambiental

Caídas	1.5 m
Caída con base de carga	1 m
Descarga electrostática (ESD)	±8 kV (descarga en aire), ±4 kV (descarga directa)
Humedad	5 % al 95 % (sin condensación)
Grado de protección IP	IP52
Temperatura de funcionamiento	De -20 °C a 60 °C (de -4 °F a 140 °F)
Temperatura de almacenamiento	De -40 °C a 70 °C (de -40 °F a 158 °F)

Software

Herramientas de configuración	EasySet
-------------------------------	---------

Certificados

Certificaciones Hardware	CE EMC Class B, FCC Part15 Class B
--------------------------	------------------------------------

Garantía

Garantía estándar	3 años
-------------------	--------

Accesorios

Accesorios opcionales	Cable RS-232
-----------------------	--------------

Accesorios estándar	Cable USB, Adaptador, Base de carga
---------------------	-------------------------------------

Newland AIDC EMEA

Feel free to contact us or a partner near you.

info@newland-id.com - newland-id.com

Specifications are subject to change without notice

© Newland AIDC EMEA 2026 - All rights reserved