



SD35 Leo

Terminales portátiles

-  1.5m drop
-  1D & 2D
-  3.5" screen
-  4G
-  5,200 mAh
-  Android 8.1
-  Bluetooth 4.1
-  Camera
-  GPRS
-  IP65
-  Laser aimer
-  Location
-  Megapixel
-  Micro SD
-  NFC
-  Touchscreen
-  USB-C
-  Warranty 2 Years
-  WIFI Dual Band



Features

Supports.
1D and 2D barcodes

Software.
Built on Android 8.1

Display.
3.5 inch (640 x 960) high-definition screen

Processor.
Octa core 2.0GHz CPU

Memory.
2GB RAM and 16GB ROM memory

Offers.
Wi-Fi 802.11 a/b/g/n (2.4GHz & 5GHz), Bluetooth 4.1, camera, NFC, GSM, WCDMA

2 Years Full Warranty

TECHNICAL SPECIFICATIONS

SD35 Leo

Captura de datos

1D	Auspost, Bpo, Canpost, Codabar, Code11, Code128, Code32, Code39, Code93, Dutchpost, Ean13, Ean8, Ean128, Int25, Isbt, Iata25, Japost, Msi, Ocr, Planet, Postnet, Strt25, Tlc39, Trioptic, Upca, and Upce
2D	Aztec, Codablock, Code49, Composite, Datamatrix, Maxicode, Micropdf, Pdf417, Qr, and Rss

Rendimiento

Sistema operativo actual	Android 8.1
Memoria flash	16GB
Memoria RAM	2GB
Procesador	2.0 GHz octa-core

Físico

Audio	Altavoces estéreo frontales dobles, Volumen: 90 dB ± 3 dB (distancia de prueba: 10 cm)
Tipo de batería	5200 mAh
Botones	Keyboard, volume buttons, power button, unction buttons (left and right)
Dimensiones (mm)	184(W) x 70(D) x 29.8(H) mm
Pantalla	3.5" (640 x 960), IPS highlight screen
Ranura de expansión	1 Micro PSAM and 1 Micro SD card up to 128 GB
Tiempo de carga previsto	PE fast charging, full charge time < 4h
Interfaces	USB-C, OTG
Teclado	40 teclas
Notificaciones	LED, Vibración, Sonido
Cámara trasera	13 MP, Enfoque automático, Flash LED de alta intensidad
SIM/TF	2 Micro SIM
Panel táctil	Pantalla táctil capacitiva de 5 puntos
Peso	290 g (with battery)

Inalámbrico

GPS	GPS, BD, GLONASS
NFC	ISO1443A/B, ISO15693, NFC reading distance: 0 to 5cm
RADIO WLAN	IEEE 802.11 a/b/g/n 2.4G 5G dual frequency
RADIO WPAN	Bluetooth 4.1 BLE
RADIO WWAN	FDD-LTE B1/B3/B7 TDD-LTE B38/B39/B40/B41 TDSCDMA B34/B39 WCDMA B1/B2/B5/B8 CDMA1x/CDMA2000 BCO

Medioambiental

Caídas	6 sides can withstand the impact of 1.5 meters drop to concrete
Descarga electrostática (ESD)	±8 kV (descarga por contacto), ±16 kV (descarga en aire)
Humedad	5 % al 95 %
Grado de protección IP	IP65
Temperatura de funcionamiento	De -20 °C a 60 °C (de -4 °F a 140 °F)
Temperatura de almacenamiento	De -30 °C a 80 °C (de -22 °F a 176 °F)

Certificados

Certificaciones Hardware	FCC, CCC, CTA, CE
--------------------------	-------------------

Garantía

Garantía estándar	2 años
-------------------	--------



Newland AIDC EMEA

Feel free to contact us or a partner near you.

info@newland-id.com - newland-id.com

Specifications are subject to change without notice

© Newland AIDC EMEA 2026 - All rights reserved