



# NLS-WCD10-1C Charging Cradle for WD1

Bases y soportes

## Features

### Professional and Reliable Design.

The cradle has a simple and reliable design, which helps to fit the WD1 Wearable Scanner perfectly into the charging slot. The cradle ensures that WD1 is in good contact and stable charging.

### Simultaneous Charging for Multi-terminals.

Each cradle can support one WD1 charging at the same time. A maximum of five cradles can be linked.

**1** Year Full  
Warranty

## TECHNICAL SPECIFICATIONS

### NLS-WCD10-1C Charging Cradle for WD1

#### Físico

Adaptador CA	DC 19V 3.2A for spliced cradles
Dimensiones (mm)	90(L)*70(W)*37(H) mm
Tiempo de carga previsto	WD1≤3.5H (DC 19V 3.2A)
Notificaciones	LED
Peso	170g

#### Medioambiental

Caídas	1.0m drops to concrete (for six sides, one drop per side)
Descarga electrostática (ESD)	±8 kV (descarga directa), ±12 kV (descarga en aire)
Humedad	5 % al 95 % (sin condensación)
Grado de protección IP	IP30
Temperatura de funcionamiento	De 5 °C a 45 °C (de -32 °F a 113 °F)
Temperatura de almacenamiento	De -30 °C a 60 °C (de -22 °F a 140 °F)

#### Garantía

Garantía estándar	1 año
-------------------	-------



**Newland AIDC EMEA**

Feel free to contact us or a partner near you.

[info@newland-id.com](mailto:info@newland-id.com) - [newland-id.com](http://newland-id.com)

Specifications are subject to change without notice

© Newland AIDC EMEA 2026 - All rights reserved