



HR33 Marlin AI Bluetooth White

Escáneres de mano



Features

Easily replaceable battery.

The HR33 Marlin AI Bluetooth White offers over 12 hours of continuous use on a single charge. If the battery runs out, the compartment features a latch-release opening for convenient replacement without interrupting your tasks. Additionally, the low-battery indicator features two colors, providing a quick visual cue when it's time to change the battery. The new magnetic contact on the stand ensures easy connectivity and high reliability.

High Connectivity.

The HR33 Marlin AI Bluetooth White scanner boasts Bluetooth 5.0 connectivity and can scan items within a range of 100 meters in open spaces. Whether you connect the communication and charging stand directly to a device via Bluetooth or use it with a dongle, the Marlin ensures a reliable wireless connection.

AI-Powered Scanning Technology.

The HR33 Marlin AI White Series is equipped with Newland's UIMG and AI-Powered Barcode Detection scanning technologies. These advanced systems enable rapid, accurate, and reliable decoding of both 1D and 2D barcodes, even when damaged or distorted, and on reflective and curved surfaces. AI-powered devices use computer vision and self-learning to interpret barcodes accurately. They efficiently analyze images to detect, locate, and read barcodes. The HR33 Marlin AI White Series excels in challenging conditions, demonstrating advanced decoding performance and providing a reliable scanning solution that functions flawlessly in any situation.

Scan & send or collect & send.

The HR33 Marlin AI Bluetooth White scanner features configurable modes that enable users to perform real-time scans and send data wirelessly. Additionally, it offers two types of offline storage for batch data sending. The scanner's memory can store thousands of codes, if necessary.

Precision and Performance.

The HR33 Marlin AI Bluetooth White is a powerful barcode scanning device. It includes an LED aimer for precise barcode scanning and a megapixel sensor that can read various types of barcodes, including damaged or distorted ones. These capabilities make it well-suited for high-density workloads. Additionally, the Marlin White Series is equipped with advanced Optical Character Recognition (OCR) technology for efficient data recognition and supports Digimarc digital watermark technology, further enhancing scanning efficiency.

Advanced Scripting.

The HR33 Marlin AI White Series scanner features Advanced Scripting, allowing users to customize and automate the scanner's behavior by writing scripts in the programming language, Lua. This capability enables users to control how the scanner processes and interprets barcode data. While EasySet remains available for those who prefer it, the addition of Advanced Scripting provides even greater detail and customization. As a result, the HR33 Marlin AI White Series is considered the best in its class.

Be confident with Newland.

The HR33 Marlin AI White Series offers users confidence with an IP52 rating, a 1.8m drop specification, and a 5-year warranty. Newland AIDC EMEA presents a scanner that's up for the job, no matter the environment.

TECHNICAL SPECIFICATIONS

HR33 Marlin AI Bluetooth White

Captura de datos

1D	Code 11, Code 128, Code39, GS1-128(UCC/ENA-128), AIM 128, ISBT 128,Codabar, Code 93, UPC-A, UPC-E, Coupon, GSI Composite, EAN-13, EAN-8, ISSN, ISBN, Interleaved 2 of 5, Matrix 2 of 5, Industrial 2 of 5, IT F-6, ITF-14, Standard 2 of 5,China Post 25, MSI-Plessey, Plessey, GS1Databar(RSS), Code 49, Code 16K.
2D	PDF417,QR Code, Micro QR, Data Matrix, Aztec, Maxi Code, Chinese Sensible Code, GM Code, Micro PDF417, Code One, Dotcode, Digimarc
Puntero	LED
Profundidad de campo Code 39 (5mil)	30 mm - 270 mm
Profundidad de campo Data Matrix (10mil)	20 mm - 245 mm
Profundidad de campo EAN 13 (13 mil)	35 mm - 535 mm
Profundidad de campo PDF417 (6.7mil)	35 mm - 215 mm
Campo de visión horizontal	48°
Campo de visión vertical	30°
Iluminación	LED blanco
Sensor de imagen	1280 x 800 CMOS
Contraste de impresión mínimo	15%
OCR	Default: Passport OCR,Chinese ID Card, China Travel Permit OCR. Optional: date and general alphanumeric recognition.
Resolución	≥3mil
Inclinación del ángulo de escaneado	±60°
Balaneo del ángulo de escaneado	360°
Sesgo del ángulo de escaneado	±65

Rendimiento

Memoria flash	≥16 384 entradas de código (de más de 60 bytes)
---------------	---

Físico

Tipo de batería	2,600 mAh lithium-ion
Dimensiones (mm)	Scanner: 117.5(L)×67.5(W)×144(H)mm; Cradle: 140(L)×90(W)×144.5(H)mm
Autonomía de la batería prevista	≥15 hours of continuous operation (scan once per 6 seconds)
Tiempo de carga previsto	≤6 hours
Carcasa	Recubrimiento antimicrobiano
Tensión de entrada	5 V CC ±5 %
Interfaces	USB-A, HID-POS, USB-CDC, USB-KBW
Notificaciones	Pitido, LED, Vibración
Peso	Scanner: 210 g; Cradle: 340,5 g

Inalámbrico

Modos de comunicación	Sincrónico, Asíncrono, Lote
Tecnología de radio	Bluetooth 5.0
Distancia inalámbrica (máx.)	≥100 m (in open space)

Medioambiental

Temperatura de carga	De 0 °C a 45 °C (de 32 °F a 113 °F)
Caídas	1.8m drops to concrete
Descarga electrostática (ESD)	±8 kV (descarga por contacto), ±15 kV (descarga en aire)
Humedad	5 % al 95 % (sin condensación)
Grado de protección IP	IP52
Temperatura de funcionamiento	De -20 °C a 50 °C (de -4 °F a 122 °F)
Temperatura de almacenamiento	De -40 °C a 70 °C (de -40 °F a 158 °F)

Software

Herramientas de configuración	EasySet
-------------------------------	---------

Certificados

Certificaciones Hardware	FCC ID, RoHS 2.0, CE RED, IEC 60825, IEC 62471
--------------------------	--

Garantía

Garantía estándar	5 años
-------------------	--------

Accesorios

Accesorios opcionales	Soporte de pared
Accesorios estándar	Cable USB, Soporte/base de conexión

¿Qué incluye la caja?

NLS-HR3300-V2-BT-W	HR33 Marlin AI Bluetooth Healthcare, Stand/docking station
--------------------	--

Accessories

Bases y soportes	NLS-STD23-33-SA-W White Smart Adjustable Stand for HR23 and HR33 Series (NLS-STD23-33-SA-W)
------------------	---



Newland AIDC EMEA
Feel free to contact us or a partner near you.
info@newland-id.com - newland-id.com

Specifications are subject to change without notice
© Newland AIDC EMEA 2026 - All rights reserved