










HR15 Wahoo Corded

Lecteurs manuels

					
1.5m drop	1D	CCD	Coiled cable	Dual Interface	IP54


Warranty 5 Years



Features

Data Acquisition.

The HR15 Wahoo Corded handheld scanner is the corded model of HR15 Wahoo series and comes with a coiled cable. It supports common 1D barcodes and PDF417 and MicroPDF417 stacked 2D barcodes.

Lightweight ergonomic design.

This corded handscanner lies comfortably in your hand and enables all day scanning comfort in scan-intensive situations. This helps reduce fatigue and protects the workforce productivity.

Interface.

The HR15 Wahoo Corded supports standard RS-232 and USB interfaces.

Durable Construction.

The HR15 Wahoo Corded was created to perform in harsh and demanding environments. With a sealing of IP54, this handheld scanner is protected against dust and moisture. With a drop resistance of 1.5m, it can withstand everyday drops and bumps.

Application scenarios.

With good performance, this rugged and compact scanner is suitable for applications in supermarkets, shopping malls, warehouse environment application and more.

5 Years Full
Warranty

TECHNICAL SPECIFICATIONS

HR15 Wahoo Corded

Capture de données

1D	All major 1D symbologies, including Code 128, EAN-13, EAN-8, Code39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5, ISBN, Code 93, UCC/EAN-128, GS1 Databar, PDF417 (max. 255 bytes), MicroPDF417 (max. 255 bytes).
Profondeur de champ	31.5 mm - 465.6 mm
Champ de vision horizontal	42°
Éclairage	LED rouge (620 nm)
Capteur d'image	2500 CCD
Contraste d'impression minimal	25%

Angle de basculement de la lecture	±55°
Angle de rotation de la lecture	30°
Angle d'inclinaison de la lecture	±75°
Modes de lecture	Mode de déclenchement, Mode Détection, Mode de détection différée, Mode manuel, Mode continu, Mode automatique, Mode clignotant
Taux de lecture	300 scans per second

Caractéristiques physiques

Courant de 5 V CC en fonctionnement	135 mA (typical), 185 mA (max)
Courant de 5 V CC en veille profonde	75 mA
Dimensions (mm)	113.5(W) x 73.3(D) x 159(H) mm
Boîtier	PC, ABS
Tension d'entrée	5 VCC ±5 %
Interfaces	USB, RS-232
Notifications	Bip, LED
Entrée alimentation	5 VDC (1.5 A)
Sortie alimentation	AC100 to 240 V (50 to 60 Hz)
Poids	152 g

Environnement

Résistance aux chutes	1.5 m
Décharge électrostatique (ESD)	±8 kV (décharge par contact), ±15 kV (décharge dans l'air)
Humidité	5 % à 95 % (sans condensation)
Indice de protection	IP54
Température de fonctionnement	de -20 °C à 50 °C (de -4 °F à 122 °F)
Température de stockage	de -20 °C à 60 °C (de -4 °F à 140 °F)

Certifications

Certifications Matériel	CE EMC Class B, FCC Part15 Class B, IEC 62471, RoHS, KC
-------------------------	---

Garantie

Contrat de service complet	3 ans, 5 ans
Garantie standard	5 ans

Accessoires

Accessoires en option	Câble USB, Câble USB-C, Adaptateur multiprise, Câble RS-232, Clip de fixation murale, Support intelligent pliable
Accessoires standard	Câble USB

Qu'y a-t-il dans la boîte ?

NLS-HR1550-35	HR15 Wahoo, 3,5 meter coiled USB cable
NLS-HR1550-35F	HR15 Wahoo, 3,5 meter coiled USB cable, Foldable smart stand
NLS-HR1550-37	HR15 Wahoo, 2 meter RS-232 cable
NLS-HR1550-38	HR15 Wahoo, 2 meter RS-232 cable, Multiplug adapter

Accessories

Charge/Alimentation

ADP100 Power Supply for HR, FR, and FM Series (ADP100)

Câbles

CBL017U RJ to USB-C Cable for HR, FR and FM Series (CBL017U)
CBL030UA USB Cable for HR12, HR32 and HR52 Series (CBL030UA)
CBL036UA USB Cable for HR, FM, and FR Series (CBL036UA)
CBL037R RS232 Cable for HR, FR, and FM Series (CBL037R)
CBL042UA USB Cable for HR, FM, and FR Series (CBL042UA)
CBL048U USB Cable for Ingenico iCT220 (CBL048U)
CBL105U USB White Cable for HR Series (CBL105U)
CBL128R Cable for Magellan Connection (CBL128R)

Périphériques

EX232 Remora (NLS-EX232-01)

Socles et supports

NLS-STD-WM001 Wall Mount Clip for HR Series (NLS-STD-WM001)
NLS-STD20I-32 Smart Foldable Stand for HR15 to HR32 Series (NLS-STD20I-32)

Newland AIDC EMEA

Feel free to contact us or a partner near you.

info@newland-id.com - newland-id.com

Specifications are subject to change without notice

© Newland AIDC EMEA 2026 - All rights reserved