

















NQquire 800 Plus

Micro Kiosques

			8,000 mAh	8.0" screen	
1.2m drop	1D & 2D	3G			Bluetooth 4.0
					
Camera	CMOS	GPS	IP67	Micro SD	Micro USB
					
Touchscreen	Warranty 2 Years	WIFI Dual Band	Windows		



Features

Integrated barcode scanner.

With built-in barcode scanners, look to the NQquire 800 Plus as the perfect solution for your business. Work faster, more efficiently and more effectively.

Impact protection.

Rigorously designed and drop tested up to 1.2M, the NQquire 800 Plus is protected from accidental bumps with reinforced edge and corner protection.

IP67 Certified.

For complete peace-of-mind, IP67 certification ensures that the device is dust proof and can be submerged into water up to 1 meter for 30 minutes.

Connectivity assured.

Always keep connected wherever your team is based with Bluetooth 4.0, a 3G micro-SIM card slot and Wi-Fi 802.11 ac/a/b/g/n connectivity. GPS tracking lets your team use location-based apps for increased accuracy and security wherever they are.

Easy-hold hand strap.

The NQquire 800 Plus easy-hold hand strap has a fully removable back plate that securely screws into the tablet's main body. With 360-degree rotation, users can position their tablet in either vertical or horizontal orientation for ease of use.

Built-in Stylus.

A discreet built-in capacitive stylus provides precision navigation and is designed to aid the function of any workforce.

2 Years Full Warranty

TECHNICAL SPECIFICATIONS

NQquire 800 Plus

Capture de données

1D	All major 1D symbologies, including Code 128, EAN-13, EAN-8, Code 39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5, ITF-6, ITF-14, ISBN, Code 93, UCC / EAN-128, GS1 Databar, Matrix 2 of 5, Code 11, Industrial 2 of 5, Standard 2 of 5, Plessey, MSI-Plessey.
2D	All major 2D symbologies, including PDF417, Data Matrix ECC200 / 000 / 050 / 080 / 100 / 140, QR Code.

Performance

Système d'exploitation actuel	64Bit Windows 10 Pro
Mémoire flash	64 Go
Mémoire RAM	4 Go
Extension de la mémoire de stockage (max.)	Up to 128GB (supports SDHC/SDXC cards)
Processeur	1.44 GHz up to 1.92 GHz, 64-Bit Quad Core; Chip: Intel Atom® x5-Z8350

Caractéristiques physiques

Prise Jack audio	prise jack 3,5 mm
Type de batterie	8000 mAh Lithium-polymer
Courant de 9 V CC en fonctionnement	700 mA (typical), 1.7 A (max)
Courant de 9 V CC en veille profonde	45 mA (typical), 75 mA (max)
Dimensions (mm)	235(W) x 147(D) x 22(H) mm
Écran	8" IPS (800 x 1280), luminance: 380cd/m2(typical value), contrast ratio: 600:1(min), 800:1(typical), view angle 1°~ 179°
Emplacement pour extension	Up to 128GB (supports SDHC/SDXC cards)
Durée de vie estimée de la batterie	5-7 hours; 250 Hours Standby
Caméra frontale	5 MPx, Mise au point automatique
Interfaces	Micro USB
Clavier	2 touches
Alimentation par Ethernet	802.3 af
Capteurs	Gravity Sensor, Acceleration sensor
Vidéo	HD (1280 x 720) @ 30FPS
Poids	875 g

Sans fil

GPS	GPS, GLONASS
RADIO WLAN	802.11 ac/a/b/g/n, 2.4Ghz and 5Ghz, WEP, WPA2-Personal AES, WPA2-Enterprise AES, 8-2.11x WEP with EAP method PEAP, EAP-SIM, EAP-TTLS
RADIO WPAN	Bluetooth 4.0
RADIO WWAN	3G Micro SIM (3FF); Band 900 / 2100 MHz

Environnement

Résistance aux chutes	1.2 m
Indice de protection	IP67
Température de fonctionnement	de -5 °C à 40 °C (de 23 °F à 104 °F)
Température de stockage	de -20 °C à 60 °C (de -4 °F à 140 °F)

Certifications

Certifications Matériel	IEC 60825, IEC2, FDA II, EN 60825-1
-------------------------	-------------------------------------

Garantie

Garantie standard	2 ans
-------------------	-------

Accessoires

Accessoires standard	Dragonne, Bloc d'alimentation, Stylet, Câble USB-OTG
----------------------	--



Newland AIDC EMEA

Feel free to contact us or a partner near you.

info@newland-id.com - newland-id.com

Specifications are subject to change without notice

© Newland AIDC EMEA 2026 - All rights reserved