



NLS-WCD10-1C Charging Cradle for WD1

Socles et supports

Features

Professional and Reliable Design.

The cradle has a simple and reliable design, which helps to fit the WD1 Wearable Scanner perfectly into the charging slot. The cradle ensures that WD1 is in good contact and stable charging.

Simultaneous Charging for Multi-terminals.

Each cradle can support one WD1 charging at the same time. A maximum of five cradles can be linked.

1 Year Full
Warranty

TECHNICAL SPECIFICATIONS

NLS-WCD10-1C Charging Cradle for WD1

Caractéristiques physiques

Adaptateur pour courant alternatif	DC 19V 3.2A for spliced cradles
Dimensions (mm)	90(L)*70(W)*37(H) mm
Temps de charge estimé	WD1≤3.5H (DC 19V 3.2A)
Notifications	LED
Poids	170g

Environnement

Résistance aux chutes	1.0m drops to concrete (for six sides, one drop per side)
Décharge électrostatique (ESD)	±8 kV (décharge directe), ±12 kV (décharge dans l'air)
Humidité	5 % à 95 % (sans condensation)
Indice de protection	IP30
Température de fonctionnement	de 5 °C à 45 °C (de -32 °F à 113 °F)
Température de stockage	de -30 °C à 60 °C (de -22 °F à 140 °F)

Garantie

Garantie standard	1 an
-------------------	------



Newland AIDC EMEA

Feel free to contact us or a partner near you.

info@newland-id.com - newland-id.com

Specifications are subject to change without notice

© Newland AIDC EMEA 2026 - All rights reserved