










HR15 Wahoo Corded

Scanner portatili

- 
1.5m drop
 - 
1D
 - 
CCD
 - 
Coiled cable
 - 
Dual Interface
 - 
IP54
- 
Warranty
5 Years



Features

Data Acquisition.
The HR15 Wahoo Corded handheld scanner is the corded model of HR15 Wahoo series and comes with a coiled cable. It supports common 1D barcodes and PDF417 and MicroPDF417 stacked 2D barcodes.

Lightweight ergonomic design.
This corded handscanner lies comfortably in your hand and enables all day scanning comfort in scan-intensive situations. This helps reduce fatigue and protects the workforce productivity.

Interface.
The HR15 Wahoo Corded supports standard RS-232 and USB interfaces.

Durable Construction.
The HR15 Wahoo Corded was created to perform in harsh and demanding environments. With a sealing of IP54, this handheld scanner is protected against dust and moisture. With a drop resistance of 1.5m, it can withstand everyday drops and bumps.

Application scenarios.
With good performance, this rugged and compact scanner is suitable for applications in supermarkets, shopping malls, warehouse environment application and more.

5 Years Full Warranty

TECHNICAL SPECIFICATIONS

HR15 Wahoo Corded

Capacità di decodifica

1D	All major 1D symbologies, including Code 128, EAN-13, EAN-8, Code39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5, ISBN, Code 93, UCC/EAN-128, GS1 Databar, PDF417 (max. 255 bytes), MicroPDF417 (max. 255 bytes).
Profondità di campo	31.5 mm - 465.6 mm
Campo di visuale orizzontale	42°
Illuminazione	LED rosso (620 nm)
Sensore immagine	2500 CCD
Contrasto di stampa minimo	25%

Angolo di scansione Pitch	±55°
Angolo di scansione Roll	30°
Angolo di scansione Skew	±75°
Velocità di scansione	Modalità di attivazione, Modalità Sensore, Modalità di rilevamento ritardato, Modalità manuale, Modalità continua, Modalità automatica, Modalità Blink
Velocità di scansione	300 scans per second

Caratteristiche fisiche

Corrente in esercizio @ 5VDC	135 mA (typical), 185 mA (max)
Corrente in standby @ 5VDC	75 mA
Dimensioni (mm)	113.5(W) x 73.3(D) x 159(H) mm
Rivestimento	PC, ABS
Tensione in ingresso	5 V CC ±5%
Interfacce	USB, RS-232
Notifiche	Segnale acustico, LED
Ingresso alimentazione	5 VDC (1.5 A)
Uscita di alimentazione	AC100 to 240 V (50 to 60 Hz)
Peso	152 g

Ambientale

Caduta	1.5 m
Scarica elettrostatica (ESD)	±8 kV (scarica da contatto), ±15 kV (scarica in aria)
Umidità	Da 5% a 95% (senza condensa)
Classificazione IP	IP54
Temperatura di esercizio	da -20 °C a 50 °C (da -4 °F a 122 °F)
Temperatura di stoccaggio	da -20 °C a 60 °C (da -4 °F a 140 °F)

Certificazioni

Certificazioni Hardware	CE EMC Class B, FCC Part15 Class B, IEC 62471, RoHS, KC
-------------------------	---

Garanzia

Contratto di assistenza completa	3 anni, 5 anni
Garanzia standard	5 anni

Accessori

Accessori opzionali	Cavo USB, Cavo USB-C, Adattatore multipresa, Cavo RS-232, Clip per il montaggio a parete, Supporto pieghevole
Accessori standard	Cavo USB

Cosa contiene la confezione?

NLS-HR1550-35	HR15 Wahoo, 3,5 meter coiled USB cable
NLS-HR1550-35F	HR15 Wahoo, 3,5 meter coiled USB cable, Foldable smart stand
NLS-HR1550-37	HR15 Wahoo, 2 meter RS-232 cable
NLS-HR1550-38	HR15 Wahoo, 2 meter RS-232 cable, Multiplug adapter

Accessories

Ricarica/Alimentazione

ADP100 Power Supply for HR, FR, and FM Series (ADP100)

Cavi

CBL017U RJ to USB-C Cable for HR, FR and FM Series (CBL017U)
CBL030UA USB Cable for HR12, HR32 and HR52 Series (CBL030UA)
CBL036UA USB Cable for HR, FM, and FR Series (CBL036UA)
CBL037R RS232 Cable for HR, FR, and FM Series (CBL037R)
CBL042UA USB Cable for HR, FM, and FR Series (CBL042UA)
CBL048U USB Cable for Ingenico iCT220 (CBL048U)
CBL105U USB White Cable for HR Series (CBL105U)
CBL128R Cable for Magellan Connection (CBL128R)

Periferiche

EX232 Remora (NLS-EX232-01)

Basi e supporti

NLS-STD-WM001 Wall Mount Clip for HR Series (NLS-STD-WM001)
NLS-STD20I-32 Smart Foldable Stand for HR15 to HR32 Series (NLS-STD20I-32)

Newland AIDC EMEA

Feel free to contact us or a partner near you.

info@newland-id.com - newland-id.com

Specifications are subject to change without notice

© Newland AIDC EMEA 2026 - All rights reserved