

















# FG60 Neptune

Terminale portatile

 1D & 2D	 5G	 6" screen	 6,500 mAh	 Android 11	 Bluetooth 5.1
 Camera	 GPRS	 IP67	 Laser aimer	 Megapixel	 NFC
 SD	 Touchscreen	 USB-C	 Warranty 2 Years	 WIFI Dual Band	

## Features

**Supports.**  
1D and 2D barcodes.

**Software.**  
Built on Android 11 GMS.

**Display.**  
6.0 inch (1080\*2340) 5-point capacitive touch screen.

**Processor.**  
Octa-Core 2.2 GHz CPU.

**Offers.**  
IEEE 802.11 a/b/g/n/ac (2.4 GHz/5GHz). Bluetooth 5.1, camera, GPS, NFC, GSM, WCDMA.

**2** Years Full Warranty

### TECHNICAL SPECIFICATIONS

## FG60 Neptune

#### Capacità di decodifica

1D	All major 1D symbologies
2D	All major 2D symbologies

#### Prestazioni di lettura

Sistema operativo attuale	Android 11, GMS
Memoria Flash	64GB
Memoria RAM	4GB

Processore 2.2 GHz octa-core

### Caratteristiche fisiche

Audio	Volume 90 dB ± 3 dB (distanza di prova 10 cm), Altoparlante stereo inferiore
Tipo di batteria	3.85 V, 5000 mAh, Swappable
Tasti	Volume+, Volume-, Shortcut key, Power key
Dimensioni (mm)	163(W) x 79(D) x 18(H) mm
Display	6" (1080 x 2340)
Slot di espansione	1 SD card
Tempo di ricarica previsto	Supports fast charging, full charge time
Fotocamera anteriore	8 MP, Messa a fuoco completa
Interfacce	USB-C
Tastiera	4 tasti
Notifiche	LED, Vibrazione, Suono
Fotocamera posteriore	13 MP, Flash a LED ad alta luminosità
Sensori	G-sensor, Acceleration sensor, Light sensor
SIM/TF	2 Micro SIM card
Camera montata sulla parte superiore	13 MP, Flash a LED ad alta luminosità
Touchscreen	Touchscreen capacitivo da 5 pollici
Peso	277 g

### Senza fili

GPS	GPS, BD, GLONASS
NFC	ISO14443A/B , ISO15693 , NFC Reading distance: 0 to 5cm
Radio WLAN	IEEE 802.11 a/b/g/n/ac, 2.4GHz and 5GHz
Radio WPAN	Bluetooth 5.1 BLE
Radio WWAN	FDD-LTE B1/B3/B5/B7/B8 TDD-LTE B34/B38/B39/ B40/B41 WCDMA B1/B2/B5/B8 GSM B2/B3/B5/B8 CDMA 1 x/CDMA2000 BC0/BC1 NR N1/N3/N28A/N41/N77/N78

### Ambientale

Caduta	1.8 m drop to concrete
Scarica elettrostatica (ESD)	±8 kV (scarica da contatto), ±15 kV (scarica in aria)
Umidità	Da 5% a 95%
Classificazione IP	IP67
Temperatura di esercizio	da -20 °C a 55 °C (da -4 °F a 131 °F)
Temperatura di stoccaggio	da -30 °C a 70 °C (da -22 °F a 158 °F)

### Certificazioni

Certificazioni Hardware	RoHS, CE, MIL-STD-810G
-------------------------	------------------------

### Garanzia

Garanzia standard	2 anni
-------------------	--------



**Newland AIDC EMEA**

Feel free to contact us or a partner near you.

[info@newland-id.com](mailto:info@newland-id.com) - [newland-id.com](http://newland-id.com)

Specifications are subject to change without notice

© Newland AIDC EMEA 2026 - All rights reserved