


















SD60 Pegasus II

Terminale portatile



-  1.2m drop
-  1D & 2D
-  4G
-  6" screen
-  6,000 mAh
-  Android 11
-  Bluetooth 5.0
-  Camera
-  GPRS
-  IP65
-  Laser aimer
-  Location
-  Megapixel
-  Micro SD
-  NFC
-  Touchscreen
-  USB-C
-  Warranty 2 Years


WIFI Dual Band

Features

Supports
1D and 2D barcodes.

Software.
Built on Android 11.

Display.
6.0 inch (2160 x 1080) 5 point capacitive touch screen.

Processor.
Octa core 2.0GHz CPU.

Offers.
Wi-Fi 802.11 a/b/g/n/ac (2.4GHz & 5GHz). Bluetooth 5.0, camera, GPS, NFC, GSM, WCDMA.

Accessories.
Supplied with cradle.

2 Years Full Warranty

TECHNICAL SPECIFICATIONS

SD60 Pegasus II

Capacità di decodifica

1D	Auspost, Bpo, Canpost, Codabar, Code11, Code128, Code32, Code39, Code93, Dutchpost, Ean13, Ean8, Ean128, Int25, Isbt, Iata25, Japost, Msi, Ocr, Planet, Postnet, Strt25, Tlc39, Trioptic, Upca, and Upce
2D	Aztec, Codablock, Code49, Composite, Datamatrix, Maxicode, Micropdf, Pdf417, Qr, and Rss

Prestazioni di lettura

Sistema operativo attuale	Android 11
Memoria Flash	64GB
Memoria RAM	4GB
Processore	2.0 GHz octa-core

Caratteristiche fisiche

Audio	Doppio altoparlante stereo anteriore, Volume 90 dB \pm 3 dB (distanza di prova 10 cm)
Tipo di batteria	6000 mAh
Tasti	Volume keys, function keys (1 left, 1 right), power key
Dimensioni (mm)	160(W) x 80(D) x 15.8(H) mm
Display	6.0" (2160 x 1080) IPS HD touch screen
Slot di espansione	Micro SD card slot
Tempo di ricarica previsto	PE fast charge, full charge time < 4h
Fotocamera anteriore	5 MP
Interfacce	USB-C
Tastiera	5 tasti
Notifiche	LED, Vibrazione, Suono
Fotocamera posteriore	13 MP, Messa a fuoco automatica, Flash a LED ad alta luminosità
Sensori	G-sensor, Proximity sensor, COMPASS, Ambient light sensor
SIM/TF	2 Nano SIM card slots
Touchscreen	Touchscreen capacitivo da 5 pollici
Peso	300 g (with battery)

Senza fili

GPS	GPS, BD, GLONASS
NFC	ISO14443A/B, 15015693, NFC Reading distance: 0 to 5cm
Radio WLAN	IEEE 802.11 a/b/g/n/ac 2.4G 5G dual frequency
Radio WPAN	Bluetooth 5.0
Radio WWAN	FDD-LTE B1/B3/B5/B7/B8, TDD-LTE B38/B39/B40/B41, TDSCDMA B34/B39, WCDMA B1/B2/B5/B8, GSM B2/B3/B5/B8, CDMA1x/CDMA2000 BC0/BC1

Ambientale

Caduta	1.2 meters drop to concrete floor
Scarica elettrostatica (ESD)	\pm 8 kV (scarica da contatto), \pm 15 kV (scarica in aria)
Umidità	Da 5% a 95%
Classificazione IP	IP65
Temperatura di esercizio	da -20 °C a 55 °C (da -4 °F a 131 °F)
Temperatura di stoccaggio	da -30 °C a 70 °C (da -22 °F a 158 °F)

Certificazioni

Certificazioni Hardware	CCC, CTA, CE
-------------------------	--------------

Garanzia

Garanzia standard	2 anni
-------------------	--------



Newland AIDC EMEA

Feel free to contact us or a partner near you.

info@newland-id.com - newland-id.com

Specifications are subject to change without notice

© Newland AIDC EMEA 2026 - All rights reserved