

















# HT35 Leo II

Terminale portatile

					
1.5m drop	1D & 2D	4.0" screen	4G	Android 11	Bluetooth 5.0
					
Camera	GPRS	IP65	Laser aimer	Megapixel	Micro SD
					
NFC	Touchscreen	USB-C	Warranty 2 Years	WIFI Dual Band	



## Features

**Supports.**  
1D and 2D barcodes.

**Software.**  
Built on Android 11.

**Display.**  
4 inch (480\*800) high-definition capacitive touchscreen.

**Processor.**  
Octa core 2.0GHz CPU.

**Memory.**  
3GB RAM and 32GB ROM memory.

**Offers.**  
Wi-Fi 802.11 a/b/g/n (2.4GHz & 5GHz), Bluetooth 5.0, camera, NFC, GSM, WCDMA.

**2** Years Full Warranty

### TECHNICAL SPECIFICATIONS

## HT35 Leo II

#### Capacità di decodifica

1D	All major 1D symbologies
2D	All major 2D symbologies

#### Prestazioni di lettura

Sistema operativo attuale	Android 11
Memoria Flash	32GB
Memoria RAM	3GB

Espansione di memoria (Max.)	Micro SD card slot up to 256GB
Processore	2.2 GHz octa-core
<b>Caratteristiche fisiche</b>	
Audio	Doppio altoparlante stereo anteriore, Volume 90 dB ± 3 dB (distanza di prova 10 cm)
Tipo di batteria	7.4 V, 19.24 Wh
Tasti	Power, scan keys, volume +/-
Dimensioni (mm)	196.4(W) x 74.8(D) x 26.8(H) mm
Display	4" (800 x 480), IPS highlight screen
Slot di espansione	Micro SD card slot up to 256GB
Tempo di ricarica previsto	PE fast charging, full charge time < 4h
Interfacce	Pin a molla, USB-C, OTG
Tastiera	40 tasti
Notifiche	LED, Vibrazione, Suono
Sensori	Proximity sensor, Acceleration sensor, Light sensor
SIM/TF	Nano SIM card slot *2
Touchscreen	Touchscreen capacitivo da 5 pollici
Peso	350 g (including battery)

#### Senza fili

GPS	GPS, BD, GLONASS
Radio WLAN	IEEE 802.11 a/b/g/n/ac 2.4G/5G dual band; supports fast roaming
Radio WPAN	Bluetooth 5.0 BLE
Radio WWAN	FDD LTE B1/B3/B5/B7/B8; TDD LTE B38/B39/B40/B41; WCDMA B1/B2/B5/B8; GSM B2/B3/B5/B8; CDMA1x/CDMA2000 BC0/BC1

#### Ambientale

Caduta	1.5 meter drop to marble
Scarica elettrostatica (ESD)	±8 kV (scarica da contatto), ±16 kV (scarica in aria)
Umidità	Da 5% a 95% (senza condensa)
Classificazione IP	IP65
Temperatura di esercizio	da -20 °C a 55 °C (da -4 °F a 131 °F)
Temperatura di stoccaggio	da -30 °C a 70 °C (da -22 °F a 158 °F)

#### Certificazioni

Certificazioni Hardware	FCC, CCC, CTA, CE
-------------------------	-------------------

#### Garanzia

Garanzia standard	2 anni
-------------------	--------



#### Newland AIDC EMEA

Feel free to contact us or a partner near you.

[info@newland-id.com](mailto:info@newland-id.com) - [newland-id.com](http://newland-id.com)

Specifications are subject to change without notice

© Newland AIDC EMEA 2026 - All rights reserved