


















# NQquire 350 Skate

Computer Touchscreen

 1D & 2D	 4.3" screen	 Android 7.1	 Bluetooth 4.0	 CMOS	 I/O Ctrl
 Megapixel	 Micro SD	 Ndevor	 PoE	 RFID	 Touchscreen
 USB	 Warranty 2 Years	 WIFI			



## Features

### Self-Scanning focused.

The NQquire 350 Skate is armed with a 2D omni-directional scan engine. Its megapixel scanner easily reads barcodes, no matter the size or material that it's been printed on. A 20 degree angle of the reader makes scanning larger products comfortable. For digital barcodes, this same tilt guides each user to present their smart phone at the optimal angle to combat reflection.

### Heavily customized Android OS for easy integration and Device Management.

Running on Android 7.1, the NQquire 350 Skate ensures intuitive navigation to your customers and your team. Looking up product information, scanning tickets or checking prices is quick and simple. Meanwhile software and development possibilities are as powerful and widespread as they are in larger equivalents.

### Greater visibility.

Newland's MDM Ndevor, included with each NQquire 350 Skate, makes updating and maintaining devices even easier by connecting them to a cloud-based configuration and monitoring tool.

### Endless communication possibilities.

The NQquire 350 Skate is equipped with a variety of features that make it easy to adapt the micro kiosk to your application. The device has a built-in RFID reader and data can be transmitted through Ethernet, WiFi and Bluetooth. An external USB and GPIO port provides the possibility to connect an external device, such as a handheld scanner.

### Mount anywhere.

With its small footprint and VESA 75 compliant design, the NQquire 350 Skate can be mounted on any shelf, pole or wall.

### Backwards compatible.

The NQquire 350 Skate's embedded CIT emulation program means the device can emulate the exact functions of the NQquire 200 series. Enabling prior customers to explore what's possible with Android while they continue their existing processes.

**2 Years Full Warranty**

**Ndevor**  
NEWLAND SOFTWARE

## TECHNICAL SPECIFICATIONS

# NQquire 350 Skate

### Capacità di decodifica

1D	All major 1D symbologies
----	--------------------------

2D	All major 2D symbologies
Puntatore	Diodo laser (625 ± 10 nm)
Illuminazione	LED bianco (625±10 nm)
Sensore immagine	1280x800 CMOS
Velocità di scansione	Modalità Sensore
Velocità di scansione	60 frames per second

#### Prestazioni di lettura

Sistema operativo attuale	Android 7.1
Memoria Flash	8GB
Memoria RAM	2GB
Espansione di memoria (Max.)	Micro SD up to 128GB
Processore	1.5 GHz octa-core

#### Caratteristiche fisiche

Audio	Audio stereo a due canali da 88 dB (da 850 Hz a 20 kHz)
Dimensioni (mm)	140(W) x 139.5(D) x 61(H) mm
Display	4,3" (480 x 272) TFT LCD Display
Slot di espansione	Micro SD up to 128GB
Interfacce	USB 2.0, GPIO
Consumo energetico	6 W
Power over Ethernet	802.3 af
Ingresso alimentazione	AC 110 to 220 V (50 to 60 Hz)
Uscita di alimentazione	DC12 V, 2 A
Touchscreen	Touchscreen capacitivo
Standard VESA	Complies with standard 75 bracket, enabling easy mounting on shelves and walls
Peso	403 g

#### Senza fili

RFID	ISO/IEC 14443 A/B ISO/IEC 15693; MIFARE 1K/4K; MIFARE DESFire; Sony FeliCa
Radio WLAN	IEEE 802.11a/b/g/n/ac
Radio WPAN	Bluetooth 4.0 LE

#### Ambientale

Umidità	Esercizio: Da 5% a 90% (senza condensa), Stoccaggio: Da 5% a 95% (senza condensa)
Temperatura di esercizio	da -10 °C a 50 °C (da 14 °F a 122 °F)
Temperatura di stoccaggio	da -20 °C a 60 °C (da -4 °F a 140 °F)

#### Software

Tools per la configurazione	Ndevor
MDM (certificato)	Ndevor, SOTI

#### Garanzia

Garanzia standard	2 anni
-------------------	--------



**Newland AIDC EMEA**

Feel free to contact us or a partner near you.

[info@newland-id.com](mailto:info@newland-id.com) - [newland-id.com](http://newland-id.com)

Specifications are subject to change without notice

© Newland AIDC EMEA 2026 - All rights reserved