



SD35 Leo

Terminale portatile

-  1.5m drop
-  1D & 2D
-  3.5" screen
-  4G
-  5,200 mAh
-  Android 8.1
-  Bluetooth 4.1
-  Camera
-  GPRS
-  IP65
-  Laser aimer
-  Location
-  Megapixel
-  Micro SD
-  NFC
-  Touchscreen
-  USB-C
-  Warranty 2 Years
-  WIFI Dual Band



Features

Supports.
1D and 2D barcodes

Software.
Built on Android 8.1

Display.
3.5 inch (640 x 960) high-definition screen

Processor.
Octa core 2.0GHz CPU

Memory.
2GB RAM and 16GB ROM memory

Offers.
Wi-Fi 802.11 a/b/g/n (2.4GHz & 5GHz), Bluetooth 4.1, camera, NFC, GSM, WCDMA

2 Years Full Warranty

TECHNICAL SPECIFICATIONS

SD35 Leo

Capacità di decodifica

1D	Auspost, Bpo, Canpost, Codabar, Code11, Code128, Code32, Code39, Code93, Dutchpost, Ean13, Ean8, Ean128, Int25, Isbt, Iata25, Japost, Msi, Ocr, Planet, Postnet, Strt25, Tlc39, Trioptic, Upca, and Upce
2D	Aztec, Codablock, Code49, Composite, Datamatrix, Maxicode, Micropdf, Pdf417, Qr, and Rss

Prestazioni di lettura

Sistema operativo attuale	Android 8.1
Memoria Flash	16GB
Memoria RAM	2GB
Processore	2.0 GHz octa-core

Caratteristiche fisiche

Audio	Doppio altoparlante stereo anteriore, Volume 90 dB \pm 3 dB (distanza di prova 10 cm)
Tipo di batteria	5200 mAh
Tasti	Keyboard, volume buttons, power button, unction buttons (left and right)
Dimensioni (mm)	184(W) x 70(D) x 29.8(H) mm
Display	3.5" (640 x 960), IPS highlight screen
Slot di espansione	1 Micro PSAM and 1 Micro SD card up to 128 GB
Tempo di ricarica previsto	PE fast charging, full charge time < 4h
Interfacce	USB-C, OTG
Tastiera	40 tasti
Notifiche	LED, Vibrazione, Suono
Fotocamera posteriore	13 MP, Messa a fuoco automatica, Flash a LED ad alta luminosità
SIM/TF	2 Micro SIM
Touchscreen	Touchscreen capacitivo da 5 pollici
Peso	290 g (with battery)

Senza fili

GPS	GPS, BD, GLONASS
NFC	ISO1443A/B, ISO15693, NFC reading distance: 0 to 5cm
Radio WLAN	IEEE 802.11 a/b/g/n 2.4G 5G dual frequency
Radio WPAN	Bluetooth 4.1 BLE
Radio WWAN	FDD-LTE B1/B3/B7 TDD-LTE B38/B39/B40/B41 TDSCDMA B34/B39 WCDMA B1/B2/B5/B8 CDMA1x/CDMA2000 BCO

Ambientale

Caduta	6 sides can withstand the impact of 1.5 meters drop to concrete
Scarica elettrostatica (ESD)	\pm 8 kV (scarica da contatto), \pm 16 kV (scarica in aria)
Umidità	Da 5% a 95%
Classificazione IP	IP65
Temperatura di esercizio	da -20 °C a 60 °C (da -4 °F a 140 °F)
Temperatura di stoccaggio	da -30 °C a 80 °C (da -22 °F a 176 °F)

Certificazioni

Certificazioni Hardware	FCC, CCC, CTA, CE
-------------------------	-------------------

Garanzia

Garanzia standard	2 anni
-------------------	--------



Newland AIDC EMEA

Feel free to contact us or a partner near you.

info@newland-id.com - newland-id.com

Specifications are subject to change without notice

© Newland AIDC EMEA 2026 - All rights reserved