



NLS-WCD10-1C Charging Cradle for WD1

Basi e supporti

Features

Professional and Reliable Design.

The cradle has a simple and reliable design, which helps to fit the WD1 Wearable Scanner perfectly into the charging slot. The cradle ensures that WD1 is in good contact and stable charging.

Simultaneous Charging for Multi-terminals.

Each cradle can support one WD1 charging at the same time. A maximum of five cradles can be linked.

1 Year Full
Warranty

TECHNICAL SPECIFICATIONS

NLS-WCD10-1C Charging Cradle for WD1

Caratteristiche fisiche

Adattatore per corrente alternata	DC 19V 3.2A for spliced cradles
Dimensioni (mm)	90(L)*70(W)*37(H) mm
Tempo di ricarica previsto	WD1≤3.5H (DC 19V 3.2A)
Notifiche	LED
Peso	170g

Ambientale

Caduta	1.0m drops to concrete (for six sides, one drop per side)
Scarica elettrostatica (ESD)	±8 kV (scarica diretta), ±12 kV (scarica in aria)
Umidità	Da 5% a 95% (senza condensa)
Classificazione IP	IP30
Temperatura di esercizio	da 5 °C a 45 °C (da -32 °F a 113 °F)
Temperatura di stoccaggio	da -30 °C a 60 °C (da -22 °F a 140 °F)

Garanzia

Garanzia standard	1 anno
-------------------	--------



Newland AIDC EMEA

Feel free to contact us or a partner near you.

info@newland-id.com - newland-id.com

Specifications are subject to change without notice

© Newland AIDC EMEA 2026 - All rights reserved