

HR33 Marlin AI Corded Healthcare

Scanner portatili



Features

AI-Powered Scanning Technology.

The HR33 Marlin AI Healthcare Series is equipped with Newland's UIMG and AI-Powered Barcode Detection scanning technologies. These advanced systems enable rapid, accurate, and reliable decoding of both 1D and 2D barcodes, even when damaged or distorted, and on reflective and curved surfaces. AI-powered devices use computer vision and self-learning to interpret barcodes accurately. They efficiently analyze images to detect, locate, and read barcodes. The HR33 Marlin AI HC Series excels in challenging conditions, demonstrating advanced decoding performance and providing a reliable scanning solution that functions flawlessly in any situation.

Precision and Performance.

The HR33 Marlin AI Corded Healthcare is a powerful barcode scanning device. It includes an LED aimer for precise barcode scanning and a megapixel sensor that can read various types of barcodes, including damaged or distorted ones. These capabilities make it well-suited for high-density workloads. Additionally, the Marlin HC Series is equipped with advanced Optical Character Recognition (OCR) technology for efficient data recognition and supports Digimarc digital watermark technology, further enhancing scanning efficiency.

Advanced Scripting.

The HR33 Marlin AI Healthcare Series scanner features Advanced Scripting, allowing users to customize and automate the scanner's behavior by writing scripts in the programming language, Lua. This capability enables users to control how the scanner processes and interprets barcode data. While EasySet remains available for those who prefer it, the addition of Advanced Scripting provides even greater detail and customization. As a result, the HR33 Marlin AI HC Series is considered the best in its class.

Versatile Stand Design.

The HR33 Marlin AI Healthcare Corded device can be purchased with a white smart adjustable stand. This stand is versatile, allowing users to adjust it from an upright position to a flat one, making it suitable for both desktop and wall-mounted use. Its white color ensures that it blends seamlessly into healthcare environments, providing added flexibility for the user's workspace.

Designed for Comfort.

The HR33 Marlin AI Healthcare Series is ergonomically designed for comfort, making it ideal for scan-intensive use in healthcare and retail. These scanners fit comfortably in any user's hand, minimizing fatigue during prolonged operations.

Be confident with Newland.

The HR33 Marlin AI Healthcare Corded offers users confidence with an IP52 rating, a 1.8m drop specification, and a 5-year warranty. Newland AIDC EMEA presents a scanner that's up for the job, no matter the environment.

TECHNICAL SPECIFICATIONS

HR33 Marlin AI Corded Healthcare

Capacità di decodifica

1D	Code 11, Code 128, Code39, GS1-128(UCC/ENA-128), AIM 128, ISBT 128,Codabar, Code 93, UPC-A, UPC-E, Coupon, GSI Composite, EAN-13, EAN-8, ISSN, ISBN, Interleaved 2 of 5, Matrix 2 of 5, Industrial 2 of 5, IT F-6, ITF-14, Standard 2 of 5,China Post 25, MSI-Plessey, Plessey, GS1Databar(RSS), Code 49, Code 16K.
2D	PDF417,QR Code, Micro QR, Data Matrix, Aztec, Maxi Code, Chinese Sensible Code, GM Code, Micro PDF417, Code One, TLC-39, Dotcode, Digimarc
Puntatore	LED
Profondità di campo Code 39 (5mil)	30 mm - 270 mm
Profondità di campo Data Matrix (10mil)	20 mm - 245 mm
Profondità di campo EAN 13 (13 mil)	35 mm - 535 mm
Profondità di campo PDF417 (6.7mil)	35 mm - 215 mm
Campo di visuale orizzontale	48°
Campo di visuale verticale	30°
Illuminazione	LED bianco
Sensore immagine	1280x800 CMOS
Contrasto di stampa minimo	15%
OCR	Default: Passport OCR,Chinese ID Card, China Travel Permit OCR. Optional: date and general alphanumeric recognition.
Risoluzione	≥3mil
Angolo di scansione Pitch	±60°
Angolo di scansione Roll	360°
Angolo di scansione Skew	±60°

Caratteristiche fisiche

Corrente in esercizio @ 5VDC	260 mA max
Corrente in standby @ 5VDC	100 mA
Dimensioni (mm)	117.5(L)×67.5(W)×144(H)mm
Rivestimento	Rivestimento antimicrobico
Tensione in ingresso	5 V CC ±5%
Interfacce	USB, RS-232, HID-POS, USB-CDC, USB-KBW
Notifiche	Segnale acustico, LED, Vibrazione
Peso	140 g

Ambientale

Caduta	1.8m drops to concrete
Scarica elettrostatica (ESD)	±8 kV (scarica da contatto), ±15 kV (scarica in aria)
Umidità	Da 5% a 95% (senza condensa)

Classificazione IP	IP52
Temperatura di esercizio	da -20 °C a 50 °C (da -4 °F a 122 °F)
Temperatura di stoccaggio	da -40 °C a 70 °C (da -40 °F a 158 °F)
Software	
Tools per la configurazione	EasySet
Garanzia	
Garanzia standard	5 anni
Accessori	
Accessori opzionali	Adattatore multipresa, Clip per il montaggio a parete, Supporto regolabile
Accessori standard	Cavo USB
Cosa contiene la confezione?	
NLS-HR3300-V2-S5-W	HR33 Marlin AI Corded Healthcare, 2 meter white straight USB cable
NLS-HR3300-V2-SA-W	HR33 Marlin AI Corded Healthcare, 2 meter white straight USB cable, White smart adjustable stand
NLS-HR3300-V2-S8-W	HR33 Marlin AI Corded Healthcare, 2 meter straight RS-232 cable, Multiplug adapter

Accessories

Periferiche	EX232 Remora (NLS-EX232-01)
--------------------	-----------------------------

Newland AIDC EMEA

Feel free to contact us or a partner near you.

info@newland-id.com - newland-id.com

Specifications are subject to change without notice

© Newland AIDC EMEA 2026 - All rights reserved