











HR22 Dorada II

Skanery ręczne

					
1.2m drop	1D & 2D	CMOS	CPU	Dual Interface	EasySet

	
IP42	Warranty 5 Years

Features

Supporting the step from 1D to 2D.

The HR22 Dorada II is specifically developed to provide a cost-effective scanning solution that allows customers to enjoy the capabilities of a 2D scanner for a price that the market had previously expected of 1D-only scanners.

Neat design.

The handheld scanner has a clean design that is not out of place on a countertop. The adjustable stand, as well as saving space and keeping your workspace clutter-free, is attractive enough to sit alongside POS equipment in a customer facing environment.

Aiming at the right code.

The HR22 Dorada II now uses white illumination so the red LED aimers can be even more clearly seen. Ensuring the scanner is correctly lining up the code, it adds an extra level of confidence to the user.

Durable construction.

The HR22 Dorada II has a more than suitable IP42 rating for its key applications and is drop resistant up to 1.5m. Its durable housing guarantees optimal protection so falls from desktops and countertops are no issue.

CPU decoding for more codes and more control.

The Dorada II now uses Newland CPU processor decoding. The benefits of CPU-based decoding include improved configurations for data handling, as well as retaining additional flexibility to add more barcode symbologies. This includes Italian Pharma code found in pharmaceutical sales, as well as tracking and Aztec, common in airline boarding passes, ticketing and some retail loyalty.

Handsfree scanning.

The handheld scanner is autosense ready, meaning it can switch from trigger press to handsfree by docking the scanner in the adjustable stand. Scanner available with stand as a kit.

5 Years Full Warranty



TECHNICAL SPECIFICATIONS

HR22 Dorada II

Przechwytywanie danych

1D	All major 1D symbologies, including Code 11, Code 128, Code 39, GS1-128 (UCC/EAN 128), AIM 128, ISBT 128, Codabar, Code 93, UPC-A, UPC-E, Coupon, GS1 Composite, EAN-8, EAN-13, ISBN/ISSN, Interleaved 2 of 5, Matrix 2 of 5, Industrial 25, ITF6, ITF-14, Standard 25, China Post 25, MSI Plessey, Plessey, GS1 Databar (RSS).
2D	All major 2D symbologies, including PDF417, Micro PDF417, Micro QR, QR Code, Data Matrix, Aztec.

Celowanie	Czerwona dioda LED (625 nm)
Głębina ostrości Kod 39 (5mil)	50 mm - 115 mm
Głębina ostrości Data Matrix (10mil)	35 mm - 125 mm
Głębina ostrości EAN 13 (13 mil)	50 mm - 260 mm
Głębina ostrości PDF417 (6.67mil)	50 mm - 120 mm
Głębina ostrości QR (15mil)	30 mm - 170 mm
Pole widzenia w poziomie	45°
Pole widzenia w pionie	34°
Oświetlenie	White LED
Czujnik obrazu	640 x 480 CMOS
Minimalny kontrast wydruku	20%
Nachylenie kąta skanowania	±55° (QR 15mil)
Rolka kąta skanowania	360° (QR 15mil)
Odchylenie kąta skanowania	±55° (QR 15mil)

Właściwości fizyczne

Prąd przy 5 VDC podczas pracy	190 mA (typical), 201 mA (max)
Prąd przy 5 VDC Standby	35 mA
Wymiary (mm)	145(W) × 101(D) × 68(H) mm
Napięcie wejściowe	5 V DC ±5%
Interfejsy	USB, RS-232
Powiadomienia	Sygnal dźwiękowy, LED
Pobór energii	950 mW (typical)
Waga	111 g

Środowiskowe

Światła otoczenia	od 0 do 100 000 luksów
Odporność na upadek	1.2 m
Wyładowanie elektrostatyczne (ESD)	±8 kV (wyładowanie bezpośrednie), ±15 kV (wyładowanie w powietrzu)
Wilgotność	5% do 95% (bez kondensacji)
Klasa IP	IP42
Temperatura robocza	od -20°C do 60°C (od -4°F do 140°F)
Temperatura przechowywania	od -40°C do 70°C (od -40°F do 158°F)

Oprogramowanie

Narzędzia konfiguracyjne	EasySet
--------------------------	---------

Certyfikaty

Certyfikaty Sprzęt	CE EMC Class B, FCC Part15 Class B, RoHS
--------------------	--

Gwarancja

Standardowa gwarancja	5 lat
-----------------------	-------



Newland AIDC EMEA

Feel free to contact us or a partner near you.

info@newland-id.com - newland-id.com

Specifications are subject to change without notice

© Newland AIDC EMEA 2026 - All rights reserved