



HR33 Marlin AI Bluetooth Healthcare

Skanery ręczne



Features

Easily replaceable battery.

The HR33 Marlin AI Bluetooth Healthcare offers over 12 hours of continuous use on a single charge. If the battery runs out, the compartment features a latch-release opening for convenient replacement without interrupting your tasks. Additionally, the low-battery indicator features two colors, providing a quick visual cue when it's time to change the battery. The new magnetic contact on the stand ensures easy connectivity and high reliability.

High Connectivity.

The HR33 Marlin AI Bluetooth Healthcare scanner boasts Bluetooth 5.0 connectivity and can scan items within a range of 100 meters in open spaces. Whether you connect the communication and charging stand directly to a device via Bluetooth or use it with a dongle, the Marlin ensures a reliable wireless connection.

AI-Powered Scanning Technology.

The HR33 Marlin AI Healthcare Series is equipped with Newland's UIMG and AI-Powered Barcode Detection scanning technologies. These advanced systems enable rapid, accurate, and reliable decoding of both 1D and 2D barcodes, even when damaged or distorted, and on reflective and curved surfaces. AI-powered devices use computer vision and self-learning to interpret barcodes accurately. They efficiently analyze images to detect, locate, and read barcodes. The HR33 Marlin AI HC Series excels in challenging conditions, demonstrating advanced decoding performance and providing a reliable scanning solution that functions flawlessly in any situation.

Scan & send or collect & send.

The HR33 Marlin AI Bluetooth Healthcare scanner features configurable modes that enable users to perform real-time scans and send data wirelessly. Additionally, it offers two types of offline storage for batch data sending. The scanner's memory can store thousands of codes, if necessary.

Precision and Performance.

The HR33 Marlin AI Bluetooth Healthcare is a powerful barcode scanning device. It includes an LED aimer for precise barcode scanning and a megapixel sensor that can read various types of barcodes, including damaged or distorted ones. These capabilities make it well-suited for high-density workloads. Additionally, the Marlin HC Series is equipped with advanced Optical Character Recognition (OCR) technology for efficient data recognition and supports Digimarc digital watermark technology, further enhancing scanning efficiency.

Advanced Scripting.

The HR33 Marlin AI Healthcare Series scanner features Advanced Scripting, allowing users to customize and automate the scanner's behavior by writing scripts in the programming language, Lua. This capability enables users to control how the scanner processes and interprets barcode data. While EasySet remains available for those who prefer it, the addition of Advanced Scripting provides even greater detail and customization. As a result, the HR33 Marlin AI HC Series is considered the best in its class.

Be confident with Newland.

The HR33 Marlin AI Healthcare Series offers users confidence with an IP52 rating, a 1.8m drop specification, and a 5-year warranty. Newland AIDC EMEA presents a scanner that's up for the job, no matter the environment.

TECHNICAL SPECIFICATIONS

HR33 Marlin AI Bluetooth Healthcare

Przechwytywanie danych

1D	Code 11, Code 128, Code39, GS1-128(UCC/ENA-128), AIM 128, ISBT 128,Codabar, Code 93, UPC-A, UPC-E, Coupon, GSI Composite, EAN-13, EAN-8, ISSN, ISBN, Interleaved 2 of 5, Matrix 2 of 5, Industrial 2 of 5, IT F-6, ITF-14, Standard 2 of 5,China Post 25, MSI-Plessey, Plessey, GS1Databar(RSS), Code 49, Code 16K.
2D	PDF417,QR Code, Micro QR, Data Matrix, Aztec, Maxi Code, Chinese Sensible Code, GM Code, Micro PDF417, Code One, Dotcode, Digimarc
Celowanie	LED
Głębokość ostrości Kod 39 (5mil)	30 mm - 270 mm
Głębokość ostrości Data Matrix (10mil)	20 mm - 245 mm
Głębokość ostrości EAN 13 (13 mil)	35 mm - 535 mm
Głębokość ostrości PDF417 (6.7mil)	35 mm - 215 mm
Pole widzenia w poziomie	48°
Pole widzenia w pionie	30°
Oświetlenie	Biała dioda LED
Czujnik obrazu	1280 x 800 CMOS
Minimalny kontrast wydruku	15%
OCR	Default: Passport OCR,Chinese ID Card, China Travel Permit OCR. Optional: date and general alphanumeric recognition.
Rezolucja	≥3mil
Nachylenie kąta skanowania	±60°
Rolka kąta skanowania	360°
Odchylenie kąta skanowania	±65

Wydajność

Pamięć Flash	≥16 384 wpisów kodu (ponad 60 bajtów)
--------------	---------------------------------------

Właściwości fizyczne

Typ Baterii	2,600 mAh lithium-ion
Wymiary (mm)	Scanner: 117.5(L)×67.5(W)×144(H)mm; Cradle: 140(L)×90(W)×144.5(H)mm
Oczekiwana żywotność baterii	≥15 hours of continuous operation (scan once per 6 seconds)
Oczekiwany czas ładowania	≤6 hours
Obudowa	Powłoka antybakteryjna
Napięcie wejściowe	5 V DC ±5%
Interfejsy	USB-A, HID-POS, USB-CDC, USB-KBW
Powiadomienia	Sygnał dźwiękowy, LED, Wibracja
Waga	Scanner: 210 g; Cradle: 340,5 g

Bezprzewodowy

Tryby komunikacji	Synchroniczny, Asynchroniczny, Partia
Technologię radiową	Bluetooth 5.0
Odległość bezprzewodowa (maks.)	≥100 m (in open space)

Środowiskowe

Temperatura ładowania	Od 0°C do 45°C (od 32°F do 113°F)
Odporność na upadek	1.8m drops to concrete
Wyładowanie elektrostatyczne (ESD)	±8 kV (wyładowanie kontaktowe), ±15 kV (wyładowanie w powietrzu)
Wilgotność	5% do 95% (bez kondensacji)
Klasa IP	IP52
Temperatura robocza	od -20°C do 50°C (od -4°F do 122°F)
Temperatura przechowywania	od -40°C do 70°C (od -40°F do 158°F)

Oprogramowanie

Narzędzia konfiguracyjne	EasySet
--------------------------	---------

Certyfikaty

Certyfikaty Sprzęt	FCC ID, RoHS 2.0, CE RED, IEC 60825, IEC 62471
--------------------	--

Gwarancja

Standardowa gwarancja	5 lat
-----------------------	-------

Akcesoria

Akcesoria opcjonalne	Klips do montażu ściennego
Akcesoria standardowe	Kabel USB, Podstawka/stacja dokująca

Co znajduje się w pudełku?

NLS-HR3300-V2-BT-W	HR33 Marlin AI Bluetooth Healthcare, Stand/docking station
--------------------	--

Newland AIDC EMEA

Feel free to contact us or a partner near you.

info@newland-id.com - newland-id.com

Specifications are subject to change without notice

© Newland AIDC EMEA 2026 - All rights reserved