Newland AIDC
SCANNING MADE SIMPLE

EM2037 V5

Silniki skanujące



1D & 2D

AI-Powered Barcode Detection

CMOS

Compact Size

DPM

EasySet

LED Aimer

Megapixel

OCR

Superior Level

TTL-232

USB

Warranty 2 Years





Features

6th Generation UIMG Technology.
Using Newland's advanced UIMG scanning technology, the EM2037 V5 offers exceptional performance in scanning both 1D barcodes and 2D codes, even if they are damaged or located on reflective and curved surfaces.

Megapixel Imaging and OCR.
The EM2037 V5 is equipped with advanced Megapixel imaging technology, enabling it to capture high-resolution images and barcodes quickly and easily. Additionally, it features cutting-edge OCR technology, enabling it to scan and accurately extract text. This makes the device ideal for applications that require precise data capture from IDs and documents.

AI-Powered Barcode Detection.
The EM2037 V5 is equipped with Newland's AI-Powered Barcode Detection technology, which is also found in several handheld and fixed-mount scanners in Newland's range. This advanced technology enables rapid, accurate, and reliable barcode decoding. By utilizing computer vision and self-learning capabilities, the scan engine efficiently analyzes images to detect, locate, and read barcodes. The self-learning feature enables automatic adjustments across various scenarios, enhancing the EM2037 V5's barcode decoding performance and speed.

Two Lens Configurations.
The EM2037 V5 comes in two versions: one with a Standard Range (SR) lens and another with a High Density (HD) lens. This option allows you to select the version that best suits your application's scanning requirements.

Host Interfaces and Development Tools.
The EM2037 V5 supports both USB and TTL-232 interfaces, enabling the engine to meet a variety of customer needs. It comes with an SDK and APIs that empower software developers to create their own applications. These features highlight the flexibility of the scanning engine, which is utilized across a wide range of applications.

Compact Split-Type Design.
The EM2037 V5 features a split-type design, with the imager and decoder board separated. This makes it ideal for various applications. Its compact, lightweight design ensures the scan engine can adapt to the host system, rather than requiring the host to accommodate it.

2 Years Full Warranty

EasySet

TECHNICAL SPECIFICATIONS

EM2037 V5

Przechwytywanie danych

1D	EAN 8, EAN 13, UPC E, UPC A, Code128, UCC/EAN128, I2Of5, Matrix 25, ITF14, ITF6, CodaBar, Code39, Code93, ISSN, ISBN, Code 49, Code11, Standard25, Industrial25, MSI Plessey, China Post 25, GS1 Databar, UCC/EAN Composite, Plessey, Code 16K
2D	PDF417, QR Code, Micro QR, DataMatrix, Aztec, MaxiCode, GM Code, Chinese Sensible Code, MicroPDF417 Code, Code One
Celowanie	Czerwona dioda LED, Zielona dioda LED
Głębia ostrości Kod 39 (5mil)	SR: 60 mm - 260 mm; HD: 40 mm - 130 mm
Głębia ostrości Data Matrix (10mil)	SR: 55 mm - 220 mm; HD: 35 mm - 125 mm
Głębia ostrości EAN 13 (13 mil)	SR: 60 mm - 460 mm; HD: 55 mm - 180 mm
Głębia ostrości PDF417 (6.7mil)	SR: 60 mm - 215 mm; HD: 35 mm - 120 mm
Głębia ostrości QR (15mil)	SR: 25 mm - 300 mm; HD: 25 mm - 160 mm
Digimarc	Digital watermark technology
Pole widzenia w poziomie	48˚
Pole widzenia w pionie	31˚
Oświetlenie	Biała dioda LED
Czujnik obrazu	1280 x 800 CMOS
Minimalny kontrast wydruku	25%
OCR	Default OCR: Passport; Optional OCR: date and general alphanumeric recognition Chinese ID Card, and China Travel Permit OCR.
Pocztowy	USPS Portnet, USPS Intelligent Mail, Royal Mail, USPS Planet, KIX Post, Australian Postal, Japan Post
Rezolucja	≥3mil
Nachylenie kąta skanowania	±55˚
Rolka kąta skanowania	360˚
Odchylenie kąta skanowania	±55˚

Właściwości fizyczne

Prąd przy 5 VDC podczas pracy	300 mA (typical), 696 mA (max.)
Prąd przy 5 VDC Standby	92 mA (typical)
Wymiary (mm)	39.5(W) × 25.4(D) × 20(H) mm (max.)
Napięcie wejściowe	12-pinowe złącze FPC: 3,3–5 V DC ±5%, 8-pinowe złącze DuPont: 3,3–5 V DC ±5%
Interfejsy	USB, TTL-232
Waga	11 g

Środowiskowe

Światła otoczenia	od 0 do 100 000 luksów (światło naturalne)
Wilgotność	5% do 95% (bez kondensacji)
Temperatura robocza	od -20°C do 60°C (od -4°F do 140°F)

Temperatura przechowywania	od -40°C do 70°C (od -40°F do 158°F)

Oprogramowanie

Narzędzia konfiguracyjne	EasySet

Certyfikaty

Certyfikaty Sprzęt	FCC Part15 Class B, CE EMC Class B

Gwarancja

Standardowa gwarancja	2 lata

Akcesoria

Akcesoria opcjonalne	Płytka do tworzenia oprogramowania, Kabel USB, Kabel RS-232

Newland AIDC EMEA
SCANNING MADE SIMPLE

Newland AIDC EMEA
Feel free to contact us or a partner near you.
info@newland-id.com - newland-id.com

Specifications are subject to change without notice
© Newland AIDC EMEA 2026 - All rights reserved