



# DC850 Susu 1D

Мобильные компьютеры

		2,300 mAh			LINUX
1.2m drop	1D		CCD	IP54	LINUX
					
Warranty 2 Years					

## Features

### Inventory Management Software.

The DC850 Susu 1D comes equipped with powerful, easy to use, inventory management software. With this combination of software and hardware, it is easy to efficiently manage your inventory flow

### Extended Battery Life.

Enabling you to get through the entire workday, the battery of the DC850 Susu 1D lasts up to 26 hours per charge.

### Functional Design.

With a design that is focused on the user, the DC850 Susu 1D is lightweight and well balanced in order to reduce stress and fatigue during long working hours.

### Rugged Construction.

The DC850 Susu 1D has a housing built for rough environments with an IP54 sealing and 1.2m drop rating.

### Price vs Performance.

As well as excellent performance, the DC850 Susu 1D is a durable scanning solution at a price that is suitable for your budget.

**2** Years Full  
Warranty

## TECHNICAL SPECIFICATIONS

### DC850 Susu 1D

#### Считывание данных

1D	All major 1D symbologies, including Code128, EAN EAN-13, EAN EAN-8, Code Code-39, UP UPC-A, UPC UPC-E, Codabar, ISBN/ISSN, Interleaved 2 of 5, Code 93.
----	---

#### Производительность

Текущая операционная система	Linux
Флеш-память	128 МБ
Память RAM	32 МБ
Процессор	1.0 GHz

## Физические характеристики

Тип батареи	3.7 V, 2300 mAh, Rechargeable lithium polymer battery
Размеры (мм)	168.5(W) x 65(D) x 39.5(H) mm
Дисплей	Level 8 monochrome display with resolution 160x160
Ожидаемый срок службы батареи	26 hours
Интерфейсы	USB
Клавиатура	26 клавиш
Уведомления	Динамик, Многоцветные светодиоды
Вход питания	AC 100 to 240 V (50 to 60 Hz)
Выход питания	DC5 V, 1.5 A
Вес	270 g (including battery)

## Экологический

Устойчивость к падениям	1.2 m
Электростатические разряды (ESD)	±8 кВ (прямой разряд), ±12 кВ (воздушный разряд)
Влажность	От 5 % до 95 % (без конденсации)
Рейтинг IP	IP54
Рабочая температура	от -10 °C до 50 °C (от 14 °F до 122 °F)
Температура хранения	от -20 °C до 60 °C (от -4 °F до 140 °F)

## Гарантия

Стандартная гарантия	2 года
----------------------	--------

## Аксессуары

Дополнительные аксессуары	USB-кабель, аккумулятор, Адаптер
---------------------------	----------------------------------

### Newland AIDC EMEA

Feel free to contact us or a partner near you.

[info@newland-id.com](mailto:info@newland-id.com) - [newland-id.com](http://newland-id.com)

Specifications are subject to change without notice

© Newland AIDC EMEA 2026 - All rights reserved