



NQuire 750 Stingray

Компьютеры с сенсорным экраном

					
1D & 2D	4G	7" screen	Android 7.1	Bluetooth 4.0	Camera
					
I/O Ctrl	Megapixel	Micro SD	Ndevor	NFC	PoE
					
RFID	Touchscreen	USB	Warranty 2 Years	WiFi Dual Band	



Features

Android OS.

The NQuire 750 Stingray uses Android 7.1 OS. With this reliable operating system comes a feature-rich environment for stable apps that are tried and tested. Android 7.1 is an excellent match for the applications most suited to the NQuire 750. Particularly when operating within four walls, fitting the NQuire 750's PoE (Power over Ethernet) connectivity.

Free MDM included.

The NQuire 750 Stingray comes with the option of running Newland's free MDM solution: Ndevor. As a result, the Micro Kiosk lends itself perfectly for the coordination of multiple units. Managing information from a shared database, organizing applications and settings across many individual units, as well as low-touch assistance in troubleshooting can all be managed from a centralized location.

Mount anywhere.

The NQuire 750 Stingray's slimline and lightweight design is suitable for mounting on any shelf edge. Options to mount the NQuire series range from shelf to wall and free-standing. Its classic Vesa75 configuration also ensures existing industry standard, 3rd party solutions are compatible.

Snappy Megapixel Scanning.

Barcode data capture is at the heart of Newland's Micro Kiosks and so the NQuire 750 is fitted with their own Megapixel scanning technology. This maintains high standards for the scanning of both large and small 1D & 2D barcodes. The Micro Kiosk further includes optimal settings for reading barcodes presented on smartphone and tablet screens. With the scanner set at a 20° angle, it matches the ergonomics of how the user presents codes for scanning.

Multi-purpose display.

The sharp, full-colour screen on the Stingray is perfect for running animations and live recorded videos when not actively being used. With onboard memory, expanded memory and online options, the choice of content to display is virtually limitless.

Endless communication possibilities.

With WiFi, Ethernet, Powered Ethernet (PoE) and Bluetooth, this Micro Kiosk offers a variety of standard communication possibilities. Additionally, optional 4G means that the NQuire 750 Stingray can communicate and be communicated with, no matter the circumstance. Adding to that the wide variety of data capture options, such as integrated barcode reading, MSR, NFC and low frequency RFID, application possibilities are endless. Modules can only be ordered pre-mounted to the connector on the left or right side.

2 Years Full Warranty

Ndevor
NEWLAND SOFTWARE

NQuire 750 Stingray

Считывание данных

1D	All major 1D symbologies
2D	All major 2D symbologies
Нацеливание	Лазерный диод (625±10 нм)
Подсветка	Белый светодиод (625±10 нм)
Датчик сканера	1280 x 800 CMOS
Режимы сканирования	Режим «Sense»
Скорость сканирования	60 frames per second

Производительность

Текущая операционная система	Android 7.1
Флеш-память	8 ГБ eMMC
Память RAM	2 ГБ DDR3
Расширение памяти (макс.)	Micro SD up to 128GB
Процессор	1.5 GHz octa-core, 64-bit

Физические характеристики

Аудио	Двухканальный стереозвук с уровнем громкости 82 дБ
Размеры (мм)	195(W) x 138.5(D) x 25(H) mm
Дисплей	7" (1280 x 800) IPS display
Слот расширения	Micro SD up to 128GB
Фронтальная камера	5 Мп, Фиксированная фокусировка
Входное напряжение	12 В постоянного тока (2 А)
Интерфейсы	Micro USB 2.0, USB 2.0, GPIO, OTG
Потребляемая мощность	12 W (max)
Передача питания по кабелю Ethernet	RJ45 Ethernet, 10/100/1.000BASE-T
Вход питания	AC 110 to 220 V (50 to 60 Hz)
Выход питания	DC12 V, 2 A
Датчики	Gravity Sensor
Сенсорная панель	5-точечный емкостный сенсорный экран
VESA (стандарт)	Complies with the standard VESA 75 bracket, enabling easy mounting on shelves and walls

Беспроводной

RFID	ISO/IEC 14443 A/B ISO/IEC 15693; MIFARE 1K/4K; MIFARE DESFire; Sony FeliCa (optional)
WLAN РАДИО	IEEE 802.11 a/b/g/n/ac, 2.4GHz and 5GHz (optional)
WPAN РАДИО	Bluetooth 4.0 LE, EDR + BLE (optional)

Экологический

Влажность	От 5 % до 90 % (без конденсации)
Рейтинг IP	IP54 (только передняя часть)
Рабочая температура	от -10 °C до 50 °C (от 14 °F до 122 °F)

Температура хранения

от -20 °C до 60 °C (от -4 °F до 140 °F)

Программное обеспечение

Инструменты настройки	Ndevor
Управление основными данными (MDM)	Ndevor, SOTI
Эмуляция терминала	StayLinked, Airwatch

Сертификаты

Сертификаты Оборудование	IEC 62471, RoHS, CE
--------------------------	---------------------

Гарантия

Комплексный сервисный контракт	3 года, 5 лет
Продление гарантии	+1 год, +3 года
Стандартная гарантия	2 года

Аксессуары

Дополнительные аксессуары	многофункциональный адаптер, Настольная подставка VESA 75, настенный кронштейн VESA 75, Модуль считывателя MSR, Модуль считывателя NFC, 4G-модуль, Модуль низкочастотного считывателя RFID
Стандартные аксессуары	многофункциональный адаптер, настенный кронштейн VESA 75

Что в коробке?

NLS-NQUIRE751PRW-7C	NQuire 750 Stingray, Wall mount bracket, Multiplug adapter
---------------------	--

Accessories

Подставки и крепления

STD1200 Desktop Stand for NQuire Series (STD1200)
WMB750 Wall Mount Bracket for NQuire Series (WMB750)



Newland AIDC EMEA

Feel free to contact us or a partner near you.
info@newland-id.com - newland-id.com

Specifications are subject to change without notice
© Newland AIDC EMEA 2026 - All rights reserved