



NLS-WCD10-1C Charging Cradle for WD1

Подставки и крепления

Features

Professional and Reliable Design.

The cradle has a simple and reliable design, which helps to fit the WD1 Wearable Scanner perfectly into the charging slot. The cradle ensures that WD1 is in good contact and stable charging.

Simultaneous Charging for Multi-terminals.

Each cradle can support one WD1 charging at the same time. A maximum of five cradles can be linked.

1 Year Full
Warranty

TECHNICAL SPECIFICATIONS

NLS-WCD10-1C Charging Cradle for WD1

Физические характеристики

AC адаптер	DC 19V 3.2A for spliced cradles
Размеры (мм)	90(L)*70(W)*37(H) mm
Ожидаемое время зарядки	WD1≤3.5H (DC 19V 3.2A)
Уведомления	LED
Вес	170g

Экологический

Устойчивость к падениям	1.0m drops to concrete (for six sides, one drop per side)
Электростатические разряды (ESD)	±8 кВ (прямой разряд), ±12 кВ (воздушный разряд)
Влажность	От 5 % до 95 % (без конденсации)
Рейтинг IP	IP30
Рабочая температура	от 5 °C до 45 °C (от -32 °F до 113 °F)
Температура хранения	от -30 °C до 60 °C (от -22 °F до 140 °F)

Гарантия

Стандартная гарантия	1 год
----------------------	-------



Newland AIDC EMEA

Feel free to contact us or a partner near you.

info@newland-id.com - newland-id.com

Specifications are subject to change without notice

© Newland AIDC EMEA 2026 - All rights reserved