











HR22 Dorada II

Ручные сканеры

					
1.2m drop	1D & 2D	CMOS	CPU	Dual Interface	EasySet

	
IP42	Warranty 5 Years

Features

Supporting the step from 1D to 2D.

The HR22 Dorada II is specifically developed to provide a cost-effective scanning solution that allows customers to enjoy the capabilities of a 2D scanner for a price that the market had previously expected of 1D-only scanners.

Neat design.

The handheld scanner has a clean design that is not out of place on a countertop. The adjustable stand, as well as saving space and keeping your workspace clutter-free, is attractive enough to sit alongside POS equipment in a customer facing environment.

Aiming at the right code.

The HR22 Dorada II now uses white illumination so the red LED aimers can be even more clearly seen. Ensuring the scanner is correctly lining up the code, it adds an extra level of confidence to the user.

Durable construction.

The HR22 Dorada II has a more than suitable IP42 rating for its key applications and is drop resistant up to 1.5m. Its durable housing guarantees optimal protection so falls from desktops and countertops are no issue.

CPU decoding for more codes and more control.

The Dorada II now uses Newland CPU processor decoding. The benefits of CPU-based decoding include improved configurations for data handling, as well as retaining additional flexibility to add more barcode symbologies. This includes Italian Pharma code found in pharmaceutical sales, as well as tracking and Aztec, common in airline boarding passes, ticketing and some retail loyalty.

Handsfree scanning.

The handheld scanner is autosense ready, meaning it can switch from trigger press to handsfree by docking the scanner in the adjustable stand. Scanner available with stand as a kit.

5 Years Full Warranty



TECHNICAL SPECIFICATIONS

HR22 Dorada II

Считывание данных

1D	All major 1D symbologies, including Code 11, Code 128, Code 39, GS1-128 (UCC/EAN 128), AIM 128, ISBT 128, Codabar, Code 93, UPC-A, UPC-E, Coupon, GS1 Composite, EAN-8, EAN-13, ISBN/ISSN, Interleaved 2 of 5, Matrix 2 of 5, Industrial 25, ITF6, ITF-14, Standard 25, China Post 25, MSI Plessey, Plessey, GS1 Databar (RSS).
2D	All major 2D symbologies, including PDF417, Micro PDF417, Micro QR, QR Code, Data Matrix, Aztec.

Нацеливание	Красный светодиод (625 нм)
Диапазоны декодирования Code 39 (5мил)	50 mm - 115 mm
Диапазоны декодирования Data Matrix (10мил)	35 mm - 125 mm
Диапазоны декодирования EAN13 (13 мил)	50 mm - 260 mm
Диапазоны декодирования PDF417 (6.67мил)	50 mm - 120 mm
Диапазоны декодирования QR (15мил)	30 mm - 170 mm
Горизонтальное поле обзора	45°
Вертикальное поле обзора	34°
Подсветка	White LED
Датчик сканера	640 x 480 CMOS
Минимальный контраст печати	20%
Наклон по вертикали	±55° (QR 15mil)
Боковой наклон	360° (QR 15mil)
Наклон по горизонтали	±55° (QR 15mil)

Физические характеристики

5 В постоянного тока в режиме эксплуатации	190 mA (typical), 201 mA (max)
5 В постоянного тока в режиме ожидания	35 mA
Размеры (мм)	145(W) × 101(D) × 68(H) mm
Входное напряжение	5 В постоянного тока ±5 %
Интерфейсы	USB, RS-232
Уведомления	Звуковой сигнал, LED
Потребляемая мощность	950 mW (typical)
Вес	111 g

Экологический

Окружающее освещение	от 0 до 100 000 люкс
Устойчивость к падениям	1.2 m
Электростатические разряды (ESD)	±8 кВ (прямой разряд), ±15 кВ (воздушный разряд)
Влажность	От 5 % до 95 % (без конденсации)
Рейтинг IP	IP42
Рабочая температура	от -20 °C до 60 °C (от -4 °F до 140 °F)
Температура хранения	от -40 °C до 70 °C (от -40 °F до 158 °F)

Программное обеспечение

Инструменты настройки	EasySet
-----------------------	---------

Сертификаты

Сертификаты Оборудование	CE EMC Class B, FCC Part15 Class B, RoHS
--------------------------	--

Гарантия

Стандартная гарантия	5 лет
----------------------	-------



Newland AIDC EMEA

Feel free to contact us or a partner near you.

info@newland-id.com - newland-id.com

Specifications are subject to change without notice

© Newland AIDC EMEA 2026 - All rights reserved