

HR33 Marlin AI Bluetooth

Ручные сканеры



Features

Easily replaceable battery.

The HR33 Marlin AI Bluetooth offers over 12 hours of continuous use on a single charge. If the battery runs out, the compartment features a latch-release opening for convenient replacement without interrupting your tasks. Additionally, the low-battery indicator features two colors, providing a quick visual cue when it's time to change the battery. The new magnetic contact on the stand ensures easy connectivity and high reliability.

High Connectivity.

The HR33 Marlin AI Bluetooth scanner boasts Bluetooth 5.0 connectivity and can scan items within a range of 100 meters in open spaces. Whether you connect the communication and charging stand directly to a device via Bluetooth or use it with a dongle, the Marlin ensures a reliable wireless connection.

AI-Powered Scanning Technology.

The HR33 Marlin AI Series is equipped with Newland's UIMG and AI-Powered Barcode Detection scanning technologies. These advanced systems enable rapid, accurate, and reliable decoding of both 1D and 2D barcodes, even when damaged or distorted, and on reflective and curved surfaces. AI-powered devices use computer vision and self-learning to interpret barcodes accurately. They efficiently analyze images to detect, locate, and read barcodes. The HR33 Marlin AI Series excels in challenging conditions, demonstrating advanced decoding performance and providing a reliable scanning solution that functions flawlessly in any situation.

Scan & send or collect & send.

The HR33 Marlin AI Bluetooth scanner features configurable modes that enable users to perform real-time scans and send data wirelessly. Additionally, it offers two types of offline storage for batch data sending. The scanner's memory can store thousands of codes, if necessary.

Scan with Precision.

The HR33 Marlin AI Series scanner is designed for precise barcode scanning. It features a laser aimer for accurate targeting and Acuscan aiming technology, which ensures that a single press of the trigger captures the correct barcode, even when multiple barcodes are nearby. Additionally, it comes with a megapixel sensor capable of reading various types of barcodes, including damaged or distorted ones, making it ideal for high-density workloads. The Marlin also boasts advanced OCR (Optical Character Recognition) capabilities for efficient data recognition and supports Digimarc digital watermark technology to enhance scanning efficiency further.

Advanced Scripting.

The HR33 Marlin AI Series scanner features Advanced Scripting, allowing users to customize and automate the scanner's behavior by writing scripts in the programming language, Lua. This capability enables users to control how the scanner processes and interprets barcode data. While EasySet remains available for those who prefer it, the addition of Advanced Scripting provides even greater detail and customization. As a result, the HR33 Marlin AI Series is considered the best in its class.

Be confident with Newland.

The HR33 Marlin AI Series offers users confidence with an IP52 rating, a 1.8m drop specification, and a 5-year warranty. Newland AIDC EMEA presents a scanner that's up for the job, no matter the environment.

TECHNICAL SPECIFICATIONS

HR33 Marlin AI Bluetooth

Считывание данных

1D	Code 11, Code 128, Code39, GS1-128(UCC/ENA-128), AIM 128, ISBT 128,Codabar, Code 93, UPC-A, UPC-E, Coupon, GSI Composite, EAN-13, EAN-8, ISSN, ISBN, Interleaved 2 of 5, Matrix 2 of 5, Industrial 2 of 5, IT F-6, ITF-14, Standard 2 of 5,China Post 25, MSI-Plessey, Plessey, GS1Databar(RSS), Code 49, Code 16K.
2D	PDF417,QR Code, Micro QR, Data Matrix, Aztec, Maxi Code, Chinese Sensible Code, GM Code, Micro PDF417, Code One, Dotcode, Digimarc
Нацеливание	Лазер
Диапазоны декодирования Code 39 (5мил)	30 mm - 270 mm
Диапазоны декодирования Data Matrix (10мил)	20 mm - 245 mm
Диапазоны декодирования EAN13 (13 мил)	35 mm - 535 mm
Диапазоны декодирования PDF417 (6.7мил)	35 mm - 215 mm
Горизонтальное поле обзора	48°
Вертикальное поле обзора	30°
Подсветка	Белый светодиод
Датчик сканера	1280 x 800 CMOS
Минимальный контраст печати	15%
OCR	Default: Passport OCR,Chinese ID Card, China Travel Permit OCR. Optional: date and general alphanumeric recognition.
Разрешение	≥3mil
Наклон по вертикали	±60°
Боковой наклон	360°
Наклон по горизонтали	±65

Производительность

Флеш-память	≥16 384 записи кода (более 60 байт)
-------------	-------------------------------------

Физические характеристики

Тип батареи	2,600 mAh lithium-ion
Размеры (мм)	Scanner: 117.5(L)×67.5(W)×144(H)mm; Cradle: 140(L)×90(W)×144.5(H)mm
Ожидаемый срок службы батареи	≥15 hours of continuous operation (scan once per 6 seconds)
Ожидаемое время зарядки	≤6 hours
Входное напряжение	5 В постоянного тока ±5 %
Интерфейсы	USB-A, HID-POS, USB-CDC, USB-KBW
Уведомления	Звуковой сигнал, LED, Вибрация
Вес	Scanner: 210 g; Cradle: 340,5 g

Беспроводной

Режимы связи	Синхронный, Асинхронный, Партия
Радиотехнология	Bluetooth 5.0
Расстояние беспроводной работы (макс.)	≥100 m (in open space)

Екологический

Температура заряда	От 0 °C до 45 °C (от 32 °F до 113 °F)
Устойчивость к падениям	1.8m drops to concrete
Электростатические разряды (ESD)	±8 кВ (контактный разряд), ±15 кВ (воздушный разряд)
Влажность	От 5 % до 95 % (без конденсации)
Рейтинг IP	IP52
Рабочая температура	от -20 °C до 50 °C (от -4 °F до 122 °F)
Температура хранения	от -40 °C до 70 °C (от -40 °F до 158 °F)

Программное обеспечение

Инструменты настройки	EasySet
-----------------------	---------

Сертификаты

Сертификаты Оборудование	FCC ID, RoHS 2.0, CE RED, IEC 60825, IEC 62471
--------------------------	--

Гарантия

Стандартная гарантия	5 лет
----------------------	-------

Аксессуары

Дополнительные аксессуары	Зажим для настенного крепления
Стандартные аксессуары	USB-кабель, Подставка/док-станция

Что в коробке?

NLS-HR3300-V2-BT	HR33 Marlin AI Bluetooth, USB cable, Stand/docking station
------------------	--

Accessories

Подставки и крепления

NLS-STD-WM001 Wall Mount Clip for HR Series (NLS-STD-WM001)



Newland AIDC EMEA
Feel free to contact us or a partner near you.
info@newland-id.com - newland-id.com

Specifications are subject to change without notice
© Newland AIDC EMEA 2026 - All rights reserved