

SD60 Pegasus II

Mobil bilgisayarlar



-  1.2m drop
-  1D & 2D
-  4G
-  6" screen
-  6,000 mAh
-  Android 11
-  Bluetooth 5.0
-  Camera
-  GPRS
-  IP65
-  Laser aimer
-  Location
-  Megapixel
-  Micro SD
-  NFC
-  Touchscreen
-  USB-C
-  Warranty 2 Years
-  WIFI Dual Band

Features

Supports
1D and 2D barcodes.

Software.
Built on Android 11.

Display.
6.0 inch (2160 x 1080) 5 point capacitive touch screen.

Processor.
Octa core 2.0GHz CPU.

Offers.
Wi-Fi 802.11 a/b/g/n/ac (2.4GHz & 5GHz). Bluetooth 5.0, camera, GPS, NFC, GSM, WCDMA.

Accessories.
Supplied with cradle.

2 Years Full Warranty

TECHNICAL SPECIFICATIONS

SD60 Pegasus II

Veri Yakalama

1D	Auspost, Bpo, Canpost, Codabar, Code11, Code128, Code32, Code39, Code93, Dutchpost, Ean13, Ean8, Ean128, Int25, Isbt, Iata25, Japost, Msi, Ocr, Planet, Postnet, Strt25, Tlc39, Trioptic, Upca, and Upce
2D	Aztec, Codablock, Code49, Composite, Datamatrix, Maxicode, Micropdf, Pdf417, Qr, and Rss

Performans

Mevcut İşletim Sistemi	Android 11
Flaş Bellek	64GB
RAM Bellek	4GB
İşlemci	2.0 GHz octa-core

Fiziksel

Ses	Ön çift stereo hoparlör, Ses seviyesi 90 dB ± 3 dB (test mesafesi 10 cm)
Pil Türü	6000 mAh
Düğmeler	Volume keys, function keys (1 left, 1 right), power key
Boyutlar (mm)	160(W) x 80(D) x 15.8(H) mm
Ekran	6.0" (2160 x 1080) IPS HD touch screen
Genişleme Yuvası	Micro SD card slot
Beklenen Şarj Süresi	PE fast charge, full charge time < 4h
Ön kamera	5 MP
Arayüzler	USB-C
Tuş takımı	5 tuş
Bildirimler	LED, Titreşim, Ses
Arka kamera	13 MP, Otomatik odaklama, Yüksek parlaklıklı LED flaş
Sensörler	G-sensor, Proximity sensor, COMPASS, Ambient light sensor
SIM/TF	2 Nano SIM card slots
Dokunmatik Panel	5 inç kapasitif dokunmatik ekran
Ağırlık	300 g (with battery)

Kablosuz

GPS	GPS, BD, GLONASS
NFC	ISO14443A/B, 15015693, NFC Reading distance: 0 to 5cm
WLAN RADIO	IEEE 802.11 a/b/g/n/ac 2.4G 5G dual frequency
WPAN RADIO	Bluetooth 5.0
WWAN RADIO	FDD-LTE B1/B3/B5/B7/B8, TDD-LTE B38/B39/B40/B41, TDSCDMA B34/B39, WCDMA B1/B2/B5/B8, GSM B2/B3/B5/B8, CDMA1x/CDMA2000 BC0/BC1

Çevresel

Düşme	1.2 meters drop to concrete floor
Elektrostatik Deşarj (ESD)	±8 kV (temas deşarjı), ±15 kV (hava deşarjı)
Nem	%5 ila %95
IP Sınıfı	IP65
Çalışma Sıcaklığı	-20 °C ile 55 °C (-4 °F ile 131 °F)
Depolama Sıcaklığı	-30 °C ile 70 °C (-22 °F ile 158 °F)

Sertifikalar

Sertifikalar Donanım	CCC, CTA, CE
----------------------	--------------

Garanti

Garanti Koşulları	2 yıl
-------------------	-------



Newland AIDC EMEA

Feel free to contact us or a partner near you.

info@newland-id.com - newland-id.com

Specifications are subject to change without notice

© Newland AIDC EMEA 2026 - All rights reserved