


















# SD60 Hercules RT

Mobil bilgisayarlar

-  1D & 2D
-  4G
-  6" screen
-  6,000 mAh
-  Android 8.1
-  Bluetooth 4.1
-  Camera
-  GPRS
-  IP65
-  Laser aimer
-  Location
-  Megapixel
-  Micro SD
-  NFC
-  Touchscreen
-  UHF
-  USB-C
-  Warranty 2 Years
-  WiFi Dual Band



## Features

**Supports**  
1D and 2D barcodes

**Software.**  
Built on Android 8.1

**Display.**  
6.0 inch (2160 x 1080) 5 point capacitive touch screen

**Processor.**  
Octa core 2.0GHz CPU

**Offers.**  
Wi-Fi 802.11 a/b/g/n (2.4GHz & 5GHz). Bluetooth 4.1, camera, GPS, NFC, GSM, WCDMA

**Accessories.**  
Supplied with cradle

**2** Years Full Warranty

## TECHNICAL SPECIFICATIONS SD60 Hercules RT

### Veri Yakalama

1D	Auspost, Bpo, Canpost, Codabar, Code11, Code128, Code32, Code39, Code93, Dutchpost, Ean13, Ean8, Ean128, Int25, Isbt, Iata25, Japost, Msi, Ocr, Planet, Postnet, Strt25, Tlc39, Trioptic, Upca, and Upce
2D	Aztec, Codablock, Code49, Composite, Datamatrix, Maxicode, Micropdf, Pdf417, Qr, and Rss

## Performans

Mevcut İşletim Sistemi	Android 8.1
Flaş Bellek	64GB
RAM Bellek	4GB
İşlemci	2.0 GHz octa-core

## Fiziksel

Ses	Ön çift stereo hoparlör, Ses seviyesi 90 dB ± 3 dB (test mesafesi 10 cm)
Pil Türü	PDA: built-in 6000 mAh lithium battery, un-removable, Grip: built-in 4000 mAh lithium battery, removable
Düğmeler	Volume buttons, function buttons (1 left, 1 right), power button, grip button
Boyutlar (mm)	160(W) x 80(D) x 15.8(H) mm
Ekran	6.0" (2160 x 1080) IPS HD touch screen
Genişleme Yuvası	Micro SD card slot
Beklenen Şarj Süresi	PE fast charge, full charge time < 4h
Ön kamera	5 MP
Arayüzler	USB-C
Tuş takımı	6 tuş
Bildirimler	LED, Titreşim, Ses
Arka kamera	13 MP, Otomatik odaklama, Yüksek parlaklıklı LED flaş
SIM/TF	2 Micro SIM card slots
Dokunmatik Panel	5 inç kapasitif dokunmatik ekran
Ağırlık	600 g (with battery)

## Kablosuz

GPS	GPS, BD, GLONASS
NFC	ISO14443NB, ISO15693, NFC Reading distance: 0 to 5cm; UHF, ISO18000-6C, Euro frequency (865MHz - 867MHz), Antenna: 4dBi quadrifilar antenna, Power: 5dBm~33dBm adjustable, 1dbm step, Working range: Indoor >18m, Outdoor >8m, Inventory speed: >200 tags/sec
WLAN RADIO	IEEE 802.11 a/b/g/n 2.4G 5G dual frequency
WPAN RADIO	Bluetooth 4.1 BLE
WWAN RADIO	FDD-LTE B1/B3/B5/B7, TDD-LTE B38/B39/B40/B41, TDSCDMA B34/B39, WCDMA B1/B2/B5/B8, GSM B2/B3/B5/B8, CDMA1x/CDMA2000 BC0/BC1

## UHF RFID

UHF Anteni	Antenna: 4dBi quadrifilar antenna
UHF Sıklığı	Euro frequency (865MHz - 867MHz)
UHF Protokolü	ISO18000-6C, Power: 5dBm~33dBm adjustable, 1dbm step
UHF Okuma Aralığı	Indoor >18m, Outdoor >8m
UHF Okuma Hızı	> 200 tags/sec

## Çevresel

Düşme	1 meter drop to cement floor
Elektrostatik Deşarj (ESD)	±8 kV (temas deşarjı), ±15 kV (hava deşarjı)
Nem	%5 ila %95

IP Sınıfı

IP65

Çalışma Sıcaklığı

-20 °C ile 55 °C (-4 °F ile 131 °F)

Depolama Sıcaklığı

-30 °C ile 70 °C (-22 °F ile 158 °F)

#### Sertifikalar

Sertifikalar Donanım

CCC, CE

#### Garanti

Garanti Koşulları

2 yıl



#### Newland AIDC EMEA

Feel free to contact us or a partner near you.

[info@newland-id.com](mailto:info@newland-id.com) - [newland-id.com](http://newland-id.com)

Specifications are subject to change without notice

© Newland AIDC EMEA 2026 - All rights reserved