



NLS-WCD10-1C Charging Cradle for WD1

Tabanlar ve tutucular

Features

Professional and Reliable Design.

The cradle has a simple and reliable design, which helps to fit the WD1 Wearable Scanner perfectly into the charging slot. The cradle ensures that WD1 is in good contact and stable charging.

Simultaneous Charging for Multi-terminals.

Each cradle can support one WD1 charging at the same time. A maximum of five cradles can be linked.

1 Year Full
Warranty

TECHNICAL SPECIFICATIONS

NLS-WCD10-1C Charging Cradle for WD1

Fiziksel

AC uyum	DC 19V 3.2A for spliced cradles
Boyutlar (mm)	90(L)*70(W)*37(H) mm
Beklenen Şarj Süresi	WD1≤3.5H (DC 19V 3.2A)
Bildirimler	LED
Ağırlık	170g

Çevresel

Düşme	1.0m drops to concrete (for six sides, one drop per side)
Elektrostatik Deşarj (ESD)	±8 kV (doğrudan deşarj), ±12 kV (hava deşarjı)
Nem	%5 ila %95 (yoğuşmasız)
IP Sınıfı	IP30
Çalışma Sıcaklığı	5 °C ile 45 °C (-32 °F ile 113 °F)
Depolama Sıcaklığı	-30 °C ile 60 °C (-22 °F ile 140 °F)

Garanti

Garanti Koşulları	1 yıl
-------------------	-------



Newland AIDC EMEA

Feel free to contact us or a partner near you.

info@newland-id.com - newland-id.com

Specifications are subject to change without notice

© Newland AIDC EMEA 2026 - All rights reserved