



# HR42 Halibut HD Corded

Endüstriyel El Tipi Barkod Okuyucular

- 1.8m drop
- 1D & 2D
- Acuscan
- Coiled cable
- DPM
- Dual Interface
- HD
- IP42
- Megapixel
- Nset
- Warranty 5 Years



## Features

### Scan virtually any barcode.

Streamline and optimize your production line with the HR42 Halibut HD Corded. Using advanced technology, the device enhances the scanning of virtually every 1D and 2D barcode printed on paper, plastic and metal, as well as a range of direct part marks (DPMs).

### Unrivalled performance.

With its megapixel camera, the HR42 Halibut HD Corded raises the bar for handheld scanners. It is able to read small, dense barcodes and damaged barcodes faster and more accurately, ensuring maximum productivity no matter what.

### User-friendly aiming technology.

Designed with the end user in mind, the HR42 Halibut HD Corded has a crisp and accurate laser aimer for point-and-shoot scanning.

### Rock-solid architecture.

Your employees can confidently use the Halibut HD Corded all day everyday due to its drop resistant housing (1.8m). Designed for light industrial environments, the Halibut gets the job done, even if they bump or drop it. Available with auto-sense stand for hands-free applications.

### Application scenarios.

Light-industrial applications, including electronic assembly, production line, healthcare, postal and financial.

5 Years Full  
Warranty



## TECHNICAL SPECIFICATIONS

# HR42 Halibut HD Corded

### Veri Yakalama

1D	All major 1D symbologies, including EAN-13, EAN-8, UPC-A, UPC-E, ISSN, ISBN, Codabar, Code 128, Code93, ITF-6, ITF-14, Interleaved 2 of 5, Industrial 2 of 5, Standard 2 of 5, Matrix 2 of 5, GS1 Databar, Code 39, Code 11, MSI-Plessey, Plessey.
2D	All major 2D symbologies, including PDF417, QR Code, Data Matrix, Aztec, Maxicode.
Hedefleme	Lazer diyet (650 nm)
Alan Derinliği Code 39 (5mil)	50 mm - 100 mm
Alan Derinliği Data Matrix (10mil)	40 mm - 110 mm

Alan Derinliđi EAN13 (13mil)	25 mm - 155 mm
Alan Derinliđi PDF417 (6.67mil)	40 mm - 105 mm
Alan Derinliđi QR (15mil)	35 mm - 155 mm
Yatay Grş Alanı	40.5°
Dikey Grş Alanı	30.4°
Aydınlatma	White LED
Grnt Sensr	1280 x 960 CMOS
Minimum Baskı Kontrastı	25%
Hareket Toleransı	2 m/s
Tarama Aısı Aralıđı	±50°
Tarama Yatıř Aısı	360°
Verev Tarama Aısı	±50°
Tarama Yntemleri	Algılama Modu, Srekli Mod, Seviye Modu, Toplu İř Modu
Tarama hızı	60 frames per second

### Performans

İřlemci	DDR3, 800Mhz
---------	--------------

### Fiziksel

5VDC alıřma akımı	266 mA (typical), 344 mA (max)
5VDC Bekleme akımı	109 mA
Boyutlar (mm)	115(W) x 74(D) x 161(H) mm
Kabuk	PC, ABS
Giriř Gerilimi	5 VDC ±%5
Arayzler	USB, RS-232
Bildirimler	Bip sesi, LED
Gc Tketimi	1251 mW (typical)
Gc Kaynađı Giriři	5 VDC (1.5 A)
Gc Kaynađı ıkıřı	AC100 to 240 V (50 to 60 Hz)
Ađırlık	173 g

### evresel

Dřme	1.8 m
Elektrostatik Deřarj (ESD)	±8 kV (dođrudan deřarj), ±16 kV (hava deřarji)
Nem	%5 ila %95 (yođuřmasız)
IP Sınıfı	IP42
alıřma Sıcaklıđı	-20 °C ile 50 °C (-4 °F ile 122 °F)
Depolama Sıcaklıđı	-40 °C ile 70 °C (-40 °F ile 158 °F)

### Yazılım

Yapılandırma Araları	NSet
-----------------------	------

### Sertifkalar

Sertifkalar Donanım	IEC 60825-1, CE EMC Class B, FCC Part15 Class B, RoHS, KC
---------------------	---



**Newland AIDC EMEA**

Feel free to contact us or a partner near you.

[info@newland-id.com](mailto:info@newland-id.com) - [newland-id.com](http://newland-id.com)

Specifications are subject to change without notice

© Newland AIDC EMEA 2026 - All rights reserved